

# Product data sheet

## Characteristics

# NSYPLAT1576G

Floor standing encl. polyester vers.PLAT open top  
w/ canopy 1500x750x620 IP44



Product availability: Non-Stock - Not normally stocked in distribution facility

Price\*: 1099.00 USD



### Main

|                           |  |
|---------------------------|--|
| Range                     | Thalassa   |
| Product name              | Thalassa PLA   |
| Device Application        | Multi-purpose  |
| Product or Component Type | Suitable enclosure   |
| Device short name         | PLAT   |
| Enclosure nominal height  | 59.06 In (1500 mm)   |
| Enclosure nominal width   | 29.53 In (750 mm)  |
| Enclosure nominal depth   | 24.41 In (620 mm)  |
| Enclosure mounting        | Floor-standing   |
| Device composition        | 1 top part<br>1 bottom part<br>2 side part<br>1 rear panel<br>1 door<br>1 canopy |

### Complementary

|                             |  |
|-----------------------------|--|
| Body type                   | Open top and sealed bottom part assembled with side parts                  |
| Door type                   | Plain front  |
| Number of doors             | 1  |
| Door opening side           | Reversible 120 °)  |
| Lock type                   | 4 points lock, handle with 5 mm double bar insert                          |
| Accessibility for operation | Rear<br>Top<br>Front   |
| Removable parts             | Door by hinges<br>Rear panel by fixing element<br>Canopy by fixing element |
| Material                    | Polyester reinforced with fibreglass                                       |
| Color                       | Grey (RAL 7035)  |
| Standards                   | IEC 62208  |

|                             |          |
|-----------------------------|----------|
| Product Certifications      | Veritas  |
| Electrical Insulation Class | Class II |

## Environment

|                                     |   |
|-------------------------------------|---|
| IP degree of protection             | IP44 IEC 60529 with ventilated canopy)    |
| IK degree of protection             | IK10 conforming to IEC 62262 (plain door) |
| Fire resistance                     | 1760 °F (960 °C) IEC 62208                |
| Ambient Air Temperature for Storage | -31...194 °F (-35...90 °C)                |

## Ordering and shipping details

|                       |                                       |
|-----------------------|---------------------------------------|
| Category              | 80035 - ENCLOSURE SYSTEMS FLOOR MOUNT |
| Discount Schedule     | ES1                                   |
| GTIN                  | 03606485434377                        |
| Nbr. of units in pkg. | 1                                     |
| Package weight(Lbs)   | 108.03 Lb(US) (49 kg)                 |
| Returnability         | No                                    |
| Country of origin     | ES                                    |

## Packing Units

|                        |                   |
|------------------------|-------------------|
| Unit Type of Package 1 | PCE               |
| Package 1 Height       | 60.24 In (153 cm) |
| Package 1 width        | 30.71 In (78 cm)  |
| Package 1 Length       | 25.59 In (65 cm)  |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| California proposition 65  | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation           | <a href="#">REACH Declaration</a>   |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>  |
| Mercury free               | Yes   |
| RoHS exemption information | <a href="#">Yes</a>   |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>  |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>   |

Product Life Status : **Commercialised**