

Product data sheet

Characteristics

NSYPLAT776G

Floor standing encl. polyester vers.PLAT open top
w/ canopy 750x750x620 IP44



Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 784.87 USD



Main

| | |
|---------------------------|--|
| Range | Thalassa |
| Product name | Thalassa PLA |
| Device Application | Multi-purpose |
| Product or Component Type | Suitable enclosure |
| Device short name | PLAT |
| Enclosure nominal height | 29.53 In (750 mm) |
| Enclosure nominal width | 29.53 In (750 mm) |
| Enclosure nominal depth | 24.41 In (620 mm) |
| Enclosure mounting | Floor-standing |
| Device composition | 1 top part 1 bottom part 2 side part 1 rear panel 1 door 1 canopy |

Complementary

| | |
|-----------------------------|--|
| Body type | Open top and sealed bottom part assembled with side parts |
| Door type | Plain front |
| Number of doors | 1 |
| Door opening side | Reversible 120 °) |
| Lock type | 2 points handle lock, 5 mm double-bar |
| Accessibility for operation | Rear Front Top |
| Removable parts | Door by hinges Rear panel by fixing element Canopy by fixing element |
| Material | Polyester reinforced with fibreglass |
| Color | Grey (RAL 7035) |
| Standards | IEC 62208 |

| | |
|-----------------------------|----------|
| Product Certifications | Veritas |
| Electrical Insulation Class | Class II |

Environment

| | |
|-------------------------------------|---|
| IP degree of protection | IP44 IEC 60529 with ventilated canopy) |
| IK degree of protection | IK10 conforming to IEC 62262 (plain door) |
| Fire resistance | 1760 °F (960 °C) IEC 62208 |
| Ambient Air Temperature for Storage | -31...194 °F (-35...90 °C) |

Ordering and shipping details

| | |
|-----------------------|---------------------------------------|
| Category | 80035 - ENCLOSURE SYSTEMS FLOOR MOUNT |
| Discount Schedule | ES1 |
| GTIN | 03606485434346 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 72.75 Lb(US) (33 kg) |
| Returnability | No |
| Country of origin | ES |

Packing Units

| | |
|------------------------|------------------|
| Unit Type of Package 1 | PCE |
| Package 1 Height | 30.71 In (78 cm) |
| Package 1 width | 30.71 In (78 cm) |
| Package 1 Length | 18.90 In (48 cm) |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |

Product Life Status : **Commercialised**