

# Product data sheet

## Characteristics

# NSYPLAZ12123G

Floor standing encl.polyester vers.PLAZ w/plinth  
open bottom 1250x1250x320 IP54



Product availability: Non-Stock - Not normally stocked in distribution facility

Price\*: 1819.65 USD



### Main

|                           |  |
|---------------------------|--|
| Range                     | Thalassa   |
| Product name              | Thalassa PLA   |
| Device Application        | Multi-purpose  |
| Product or Component Type | Suitable enclosure   |
| Device short name         | PLAZ   |
| Enclosure nominal height  | 49.21 In (1250 mm)   |
| Enclosure nominal width   | 49.21 In (1250 mm)   |
| Enclosure nominal depth   | 12.60 In (320 mm)  |
| Enclosure mounting        | Floor-standing   |
| Device composition        | 1 top part<br>1 bottom part<br>2 side part<br>2 door<br>2 rear panel<br>1 plinth |

### Complementary

|                             |   |
|-----------------------------|---|
| Body type                   | Sealed top and open bottom part assembled with side parts |
| Door type                   | Plain front   |
| Number of doors             | 2   |
| Door opening side           | Right and left 120 °)                                     |
| Lock type                   | 4 points lock, handle with 5 mm double bar insert         |
| Accessibility for operation | Front<br>Bottom<br>Rear                                   |
| Removable parts             | Door by hinges<br>Rear panel by fixing element            |
| Material                    | Polyester reinforced with fibreglass                      |
| Color                       | Grey (RAL 7035)   |
| Standards                   | IEC 62208   |

|                             |          |
|-----------------------------|----------|
| Product Certifications      | Veritas  |
| Electrical Insulation Class | Class II |

## Environment

|                                     |   |
|-------------------------------------|---|
| IP degree of protection             | IP54 IEC 60529 plinth type open bottom)   |
| IK degree of protection             | IK10 conforming to IEC 62262 (plain door) |
| Fire resistance                     | 1760 °F (960 °C) IEC 62208                |
| Ambient Air Temperature for Storage | -31...194 °F (-35...90 °C)                |

## Ordering and shipping details

|                       |  |
|-----------------------|--|
| Category              | 80034 - ENCLOSURE SYSTEMS WALL MOUNT METAL |
| Discount Schedule     | ES1  |
| GTIN                  | 03606480775659                             |
| Nbr. of units in pkg. | 1  |
| Package weight(Lbs)   | 129.11 Lb(US) (58.561 kg)                  |
| Returnability         | No   |
| Country of origin     | ES   |

## Packing Units

|                        |                   |
|------------------------|-------------------|
| Unit Type of Package 1 | PCE               |
| Package 1 Height       | 50.79 In (129 cm) |
| Package 1 width        | 50.39 In (128 cm) |
| Package 1 Length       | 14.96 In (38 cm)  |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| California proposition 65  | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation           | <a href="#">REACH Declaration</a>   |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>  |
| Mercury free               | Yes   |
| RoHS exemption information | <a href="#">Yes</a>   |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>  |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>   |

Product Life Status : **Commercialised**