

Product data sheet

Characteristics


NSYTBP292412HT

PC box IP66 IK08 RAL7035 Int.H275W225D120
Ext.H291W241D128 Transp.cover H60



Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 116.66 USD



Main

Range	Thalassa
Product name	Thalassa TBP
Device application	Multi-purpose
Product or component type	Industrial box
Height	11.46 In (291 mm)
Width	9.49 In (241 mm)
Depth	5.04 In (128 mm)
Internal height	10.83 In (275 mm)
Internal width	8.86 In (225 mm)
Internal depth	4.72 In (120 mm)
Enclosure mounting	Wall mounted
Device composition	1 body 1 cover 4 cover screw
Body type	One piece moulded
Type of front cover	High transparent cover
Cover fixing	Plastic screws
Lock type	Captive screw flat outside sealed area
Removable parts	Cover by captive screws

Complementary

Material	Polycarbonate
Color	Gray RAL 7035) Transparent
Standards	IEC 62208 UL 508 A
Product certifications	TÜV UL
Electrical insulation class	Class II

Mounting location	Outdoor
Net weight	2.65 Lb(US) (1.2 kg)

Environment

IP degree of protection	IP66 conforming to NEMA 4.4X
IK degree of protection	IK08 conforming to IEC 62262
Fire resistance	1760 °F (960 °C)
Ambient air temperature for storage	5...140 °F (-15...60 °C)
Ambient air temperature for operation	-13...176 °F (-25...80 °C)

Ordering and shipping details

Category	80033 - ENCLOSURE SYSTEMS POLYESTER
Discount Schedule	ES1
GTIN	03606480165894
Nbr. of units in pkg.	1
Package weight(Lbs)	2.65 Lb(US) (1.2 kg)
Returnability	No
Country of origin	HU

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	5.04 In (12.8 cm)
Package 1 width	9.49 In (24.1 cm)
Package 1 Length	11.46 In (29.1 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**