

Product data sheet

Characteristics

PGL36120U31A

MOLDED CASE CIRCUIT BREAKER 600V 1200A



Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 19836.00 USD



Main

Device short name	A
Product or component type	Circuit breaker

Complementary

Line Rated Current	1200 A
Poles description	3P
Breaking capacity code	G
Electrical connection	Lugs load Lugs line
Tightening torque	442.54 Lbf.In (50 N.m) 0.15...0.37 in ² (95...240 mm ²) (AWG 3/0...500 kcmil) 8.85...11.51 Lbf.In (1.0...1.3 N.m)
Height	16.16 In (410.46 mm)
Width	8.27 In (210.06 mm)
Depth	8.05 In (204.47 mm)
Continuous current rating	80 %

Ordering and shipping details

Category	01215 - PG,H,J,K,L,N UNIT MT BREAKERS
Discount Schedule	DE2
GTIN	00785901790495
Nbr. of units in pkg.	1
Package weight(Lbs)	32.00 Lb(US) (14.515 kg)
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	11.75 In (29.845 cm)
Package 1 width	11.63 In (29.528 cm)
Package 1 Length	20.25 In (51.435 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DIN-P, which is known to the State of California to cause cancer, and DID-P, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**