

Product data sheet

Characteristics

PJA36060U33A

Circuit breaker, PowerPact P, I-Line, Micrologic 5.0, 600A, 3 pole, 25 kA, 600 VAC, phase ABC



Price*: 16608.00 USD



Main

Device short name	A
Product or component type	Circuit breaker

Complementary

Line Rated Current	600 A
Poles description	3P
Breaking capacity code	J
Electrical connection	I-Line connection line Lugs load
Tightening torque	442.54 Lbf.In (50 N.m) 0.15...0.37 in ² (95...240 mm ²) (AWG 3/0...500 kcmil) 8.85...11.51 Lbf.In (1.0...1.3 N.m)
Height	12.86 In (326.64 mm)
Width	8.27 In (210.06 mm)
Depth	8.05 In (204.47 mm)
Continuous current rating	80 %

Ordering and shipping details

Category	01210-PG,H,J,K,L,N I-LINE BREAKERS
Discount Schedule	DE2
GTIN	00785901886594
Package weight(Lbs)	37.00 Lb(US) (16.783 kg)
Returnability	Yes
Country of origin	US

Packing Units

Package 1 Height	12.50 In (31.750 cm)
Package 1 width	12.00 In (30.480 cm)
Package 1 Length	20.50 In (52.070 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DIN-P, which is known to the State of California to cause cancer, and DID-P, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**