

# Product data sheet

## Characteristics

# PJA36120U44A

Circuit breaker, PowerPact P, I-Line, Micrologic  
6.0A, 1200A, 3 pole, 25 kA, 600 VAC, phase ABC



Product availability: Stock - Normally stocked in distribution facility

Price\*: 26211.00 USD



### Main

Device short name	A
Product or component type	Circuit breaker

### Complementary

Line Rated Current	1200 A
Poles description	3P
Breaking capacity code	J
Electrical connection	I-Line connection line Lugs load
Tightening torque	442.54 Lbf.In (50 N.m) 0.15...0.37 in <sup>2</sup> (95...240 mm <sup>2</sup> ) (AWG 3/0...500 kcmil) 8.85...11.51 Lbf.In (1.0...1.3 N.m)
Height	16.16 In (410.46 mm)
Width	8.27 In (210.06 mm)
Depth	8.05 In (204.47 mm)
Continuous current rating	80 %

### Ordering and shipping details

Category	01210 - PG,H,J,K,L,N I-LINE BREAKERS
Discount Schedule	DE2
GTIN	00785901282273
Nbr. of units in pkg.	1
Package weight(Lbs)	37.92 Lb(US) (17.2 kg)
Returnability	Yes
Country of origin	US

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	12.30 In (31.242 cm)
Package 1 width	12.10 In (30.734 cm)
Package 1 Length	20.60 In (52.324 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DIN-P, which is known to the State of California to cause cancer, and DID-P, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
PVC free	Yes

## Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**