

# PJL36000S12

## POWERPACT AUTOMATIC MOULDED CASE SWITCH 600V 1200 A P-Frame



Product availability: Stock - Normally stocked in distribution facility

Price\*: 11867.00 USD



### Main

Product or component type	Automatic switch
Range of product	PowerPact P
Trip unit technology	Magnetic
Circuit breaker type	P-frame

### Complementary

Line Rated Current	1200 A
[Ue] rated operational voltage	600 V AC
Mounting mode	Unit mount
Poles description	3P
Short-circuit withstand	65 KA 480 V UL 489 25 KA 600 V UL 489 100 KA 240 V UL 489
Breaking capacity code	J
Electrical connection	Lugs line Lugs load
AWG gauge	AWG 3/0...500 kcmil aluminium/copper)4
Terminal identifier	AL1200P25K
Magnetic tripping current	10000 A
Height	16.24 In (412.50 mm)
Width	16.54 In (420.12 mm)
Depth	14.49 In (368.05 mm)
Tightening torque	442.54 Lbf.In (50 N.m) 0.15...0.37 in <sup>2</sup> (95...240 mm <sup>2</sup> ) (AWG 3/0...500 kcmil)

### Environment

Product certifications	CSA UL Listed IEC
------------------------	-------------------------

## Ordering and shipping details

Category	01215 - PG,H,J,K,L,N UNIT MT BREAKERS
Discount Schedule	DE2
GTIN	00785901760252
Nbr. of units in pkg.	1
Package weight(Lbs)	38.93 Lb(US) (17.66 kg)
Returnability	Yes
Country of origin	US

## Packing Units

Package 1 Height	12.40 In (31.496 cm)
Package 1 width	12.00 In (30.480 cm)
Package 1 Length	20.60 In (52.324 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DIN-P, which is known to the State of California to cause cancer, and DID-P, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
PVC free	Yes

## Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**