

Product data sheet

Characteristics

QO115VHCAFI

Mini circuit breaker, QO, 15A, 1 pole, 120/240 VAC, 22 kA, combo arc fault, pigtail, plug in mount



Price*: 534.00 USD



Main

Product or component type	Miniature circuit-breaker
Range of product	QO
Line Rated Current	15 A
[Ue] rated operational voltage	120/240 V AC 120 V AC
Mounting mode	Plug-in
Poles description	1P
Circuit breaker type	Combination ARC-fault
Circuit breaker application	Not rated
Electrical connection	Pressure plate
Connections - terminals	Pigtail neutral

Complementary

Breaking capacity	22 KA 120/240 V AC 50/60 Hz 22 KA 120 V AC 50/60 Hz
Number of spaces required	1
AWG gauge	AWG 14...AWG 8 copper AWG 12...AWG 8 aluminium
Height	4.75 In (120.65 mm)
Width	0.75 In (19.05 mm)
Depth	2.91 In (73.91 mm)

Environment

Product certifications	UL Listed CSA
Ambient air temperature for operation	104 °F (40 °C)

Ordering and shipping details

Category	06303-QO ARC FAULT CB
Discount Schedule	DE2A
GTIN	00785901523192
Package weight(Lbs)	8.96 Oz (254.012 g)
Returnability	Yes
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**