

Product data sheet

Characteristics

QO1305237

Mini circuit breaker, QO, 30A, 1 pole, 120/240 VAC, 10 kA, plug in mount, ring terminals



Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 37.77 USD



Main

Product or component type	Miniature circuit-breaker
Range of product	QO
Line Rated Current	30 A
[Ue] rated operational voltage	120/240 V AC 120 V AC 48 V DC
Mounting mode	Plug-in
Poles description	1P
Circuit breaker type	Standard
Circuit breaker application	HACR rated
Electrical connection	Ring tongue

Complementary

Breaking capacity	10 KA 120/240 V AC 50/60 Hz 10 KA 120 V AC 50/60 Hz 5 KA 48 V DC
Number of spaces required	1
AWG gauge	AWG 14...AWG 8 copper or aluminium
Tightening torque	40.71 Lbf.In (4.6 N.m)
Height	3 In (76.20 mm)
Width	0.75 In (19.05 mm)
Depth	2.91 In (73.91 mm)

Environment

Product certifications	UL Listed CSA
Ambient air temperature for operation	104 °F (40 °C)

Ordering and shipping details

Category	00004 - QO,QOT 10-30A 1P;10-60A 2P
Discount Schedule	DE2A
GTIN	00785901933069
Nbr. of units in pkg.	1
Package weight(Lbs)	1 Lb(US) (0.45 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Package 1 Height	0.80 In (2.032 cm)
Package 1 width	3.50 In (8.890 cm)
Package 1 Length	3.50 In (8.890 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Halogen content performance	Halogen free product

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**