

Product data sheet

Characteristics

QO130PL

Mini circuit breaker, QO, 30A, 1 pole, 120/240 VAC, 10 kA, Powerlink, plug in mount



Price*: 224.00 USD



Main

Product or component type	Circuit breaker
Range of product	QO
Line Rated Current	30 A
[Ue] rated operational voltage	120/240 V AC
Mounting mode	Plug-in
Poles description	1P
Circuit breaker type	Standard
Circuit breaker application	HACR rated
Electrical connection	Box lugs

Complementary

Breaking capacity	10 KA 120/240 V AC 50/60 Hz
Number of spaces required	1
Provided equipment	18 In (457.20 mm) lead
AWG gauge	AWG 12...AWG 2 aluminium AWG 14...AWG 2 copper
Tightening torque	40.71 Lbf.In (4.6 N.m)
Height	4.55 In (115.57 mm)
Width	0.75 In (19.05 mm)
Depth	2.91 In (73.91 mm)

Environment

Product certifications	UL Listed CSA
Ambient air temperature for operation	104 °F (40 °C)

Ordering and shipping details

Category	09650-POWERLINK QO(B)PL BREAKERS
Discount Schedule	DE8A
GTIN	00785901096009
Nbr. of units in pkg.	1
Package weight(Lbs)	0.50 Lb(US) (0.227 kg)
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	1.30 In (3.302 cm)
Package 1 width	3.80 In (9.652 cm)
Package 1 Length	5.50 In (13.97 cm)

Offer Sustainability

California proposition 65	WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Halogen content performance	Halogen free product

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**