

Product data sheet

Characteristics

QOB260GFI

Mini circuit breaker, QO, 60A, 2 pole, 120/240 VAC, 10 kA, 6mA grd fault A, pigtail, bolt on mount



Product availability: Stock - Normally stocked in distribution facility

Price*: 444.00 USD



Main

Product or component type	Miniature circuit-breaker
Range of product	QO
Line Rated Current	60 A
[Ue] rated operational voltage	120/240 V AC
Mounting mode	Bolt-on
Poles description	2P
Circuit breaker type	Ground fault protecting class A 6 mA
Circuit breaker application	Not rated
Electrical connection	Box lugs

Complementary

Breaking capacity	10 KA 120/240 V AC 50/60 Hz 10 KA
Number of spaces required	2
AWG gauge	AWG 12...AWG 4 aluminium AWG 14...AWG 6 copper
Tightening torque	40.71 Lbf.In (4.6 N.m) 0.00...0.02 in ² (2.5...10 mm ²) (AWG 16...AWG 14) 40.71 Lbf.In (4.6 N.m) 0.01...0.03 in ² (4...20 mm ²) (AWG 12...AWG 4)
Height	4.12 In (104.65 mm)
Width	1.5 In (38.10 mm)
Depth	2.91 In (73.91 mm)

Environment

Product certifications	UL Listed CSA
Ambient air temperature for operation	104 °F (40 °C)

Ordering and shipping details

Category	00015 - QOB CIRCUIT BREAKERS
Discount Schedule	DE2
GTIN	00785901363002
Nbr. of units in pkg.	1
Package weight(Lbs)	15.68 Oz (444.521 g)
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	2.20 In (5.588 cm)
Package 1 width	3.50 In (8.89 cm)
Package 1 Length	5.30 In (13.462 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**