

Product data sheet

Characteristics

QOU2301042

Mini circuit breaker, QOU, 30A, 2 pole, 120/240 VAC, 10kA, shunt trip



Price*: 276.00 USD



Main

Product or component type	Miniature circuit-breaker
Range of product	QOU
Circuit breaker type	Standard
Circuit breaker application	HACR and Switching Duty rated

Complementary

Line Rated Current	30 A
Electrical connection	Slotted box lugs, line side Slotted box lugs, load side
[Ue] rated operational voltage	120/240 V AC 120 V AC 48 V DC
Mounting mode	Unit mount
AWG gauge	AWG 14...AWG 2 aluminium/copper
Height	4.05 In (102.87 mm)
Depth	2.95 In (74.93 mm)
Width	2.25 In (57.15 mm)
Tightening torque	45 Lbf.In (5.08 N.m) (AWG 14...AWG 2)

Environment

Product certifications	CSA IEC UL Listed
------------------------	-------------------------

Ordering and shipping details

Category	00900-QOU BREAKERS & SWITCH
Discount Schedule	DE2
GTIN	00785901586036
Package weight(Lbs)	16.96 Oz (480.808 g)
Returnability	No
Country of origin	MX

Packing Units

Package 1 Height	3.60 In (9.144 cm)
Package 1 width	2.60 In (6.604 cm)
Package 1 Length	4.80 In (12.192 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Halogen content performance	Halogen free product

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**