

Product data sheet

Characteristics

SM573B115

Hyde Park, Flat Profile Ultrasonic Sensor

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 881.00 USD

Main

Range of Product	Hyde Park
Sensor Type	Ultrasonic sensor
Series name	Standard format
Device short name	SM573
Sensor design	Compact
Material	Plastic
[Us] rated supply voltage	100...240 V AC
Electrical connection	1 connector
Product Specific Application	Other terminal unit
[Sd] sensing range	0.17...3.28 Ft (0.051...1 m)
IP degree of protection	IP66


Complementary

[Sn] nominal sensing distance	3.28 Ft (1 m)
Type of sensing window	Fixed
Transmission frequency	200 KHz

Ordering and shipping details

Category	22490 - SENSORS-ULTRASONIC (XX5,6)
Discount Schedule	DS2
GTIN	03389119095808
Nbr. of units in pkg.	1
Package weight(Lbs)	0.8 Lb(US) (0.36 kg)
Returnability	No
Country of origin	US

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	 REACH Declaration
EU RoHS Directive	Not applicable, out of EU RoHS legal scope

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**