

Product data sheet

Specifications



Socket, General Purpose Relays, for 750H/750 relays, DPDT, 8 pins, screws clamp terminals, 16A, 300V

70-750DL8-1

Product availability: Stock - Normally stocked in distribution facility

Price*: 14.95 USD

Main

Product Range	Legacy
Product Type	Socket
Product Compatibility	relay 750XCXR relay 750XCXH suppressor module 70-ASMM diode 70-ASMD signalling device 70-ASMLG suppressor module 70-ASMR jumper wire 16-750CBJ-1
Number of Terminals	8
Switch Function	DPDT
Contact Composition	2 NO + 2 NC

Complementary

Rated Current	16 A
[Ue] rated operational voltage	300 V
Contact Terminal Arrangement	Mixed
Connections Terminals	screw clamp terminals solid for output screw clamp terminals stranded for output
Tightening Torque	Chassis 0.8 N.m, AWG 14...AWG 12, copper Screw 1 N.m
Fixing Mode	By screw M3.5, M3.5 panel Clip-on 35 mm DIN rail
Shape of Screw Head	Combination roundhead
Product Weight	2.1 oz (60 g)
Width	1.4 in (36 mm)
Depth	2.9 in (72.7 mm)

Environment

Ambient Air Temperature for Storage	-40...221 °F (-40...105 °C)
Ambient Air Temperature for Operation	-40.0000000000...131.0000000000 °F (-40...55 °C)
IP Degree of Protection	IP20
Flame Retardance	UL94-V0

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Product Certifications	UL CSA CE
------------------------	-----------------

Ordering and shipping details

Category US10CP221127

Discount Schedule 0CP2

GTIN 3606480278006

Returnability Yes

Country of origin TW

Packing Units

Unit Type of Package 1 PCE

Number of Units in Package 1 1

Package 1 Height 3.05 in (7.75 cm)

Package 1 Width 1.4 in (3.6 cm)

Package 1 Length 1.4 in (3.6 cm)

Package 1 Weight 2.1 oz (60.0 g)

Unit Type of Package 2 CAR

Number of Units in Package 2 10

Package 2 Height 3.3 in (8.3 cm)

Package 2 Width 2.9 in (7.4 cm)

Package 2 Length 7.6 in (19.4 cm)

Package 2 Weight 26.1 oz (740.5 g)

Unit Type of Package 3 BB1

Number of Units in Package 3 100

Package 3 Height 16.2 in (41.2 cm)

Package 3 Width 9.06 in (23.0 cm)

Package 3 Length 16.1 in (40.9 cm)

Package 3 Weight 33.07 lb(US) (15.0 kg)

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

 Reach Free Of Svhc

 Toxic Heavy Metal Free

 Mercury Free

 RoHS Exemption Information Yes

Certifications & Standards

Reach Regulation

[REACH Declaration](#)

Eu RoHS Directive

Pro-active compliance (Product out of EU RoHS legal scope)

[EU RoHS Declaration](#)

China RoHS Regulation

[China RoHS declaration](#)

Environmental Disclosure

[Product Environmental Profile](#)

Weee

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Circularity Profile

No need of specific recycling operations

California Proposition 65

"WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](#)"