

Product data sheet

Specifications



Socket, SE Relays general purpose relay accessory, 3PDT, 16A, 300 V, 11 pins, screw clamping terminal, 784 series

70-783D11-1A

Product availability: Stock - Normally stocked in distribution facility

Price*: 13.45 USD

Main

| | |
|-----------------------|---|
| Product Range | Legacy |
| Product Type | Socket |
| Product Compatibility | relay 783XCX suppressor module 70-ASMM diode 70-ASMD signalling device 70-ASMLG suppressor module 70-ASMR |
| Number of Terminals | 11 |
| Switch Function | 3PDT |
| Contact Composition | 3 NO + 3 NC |

Complementary

| | |
|--------------------------------|---|
| Rated Current | 16 A |
| [Ue] rated operational voltage | 300 V |
| Contact Terminal Arrangement | Mixed |
| Connections Terminals | screw clamp terminals solid for output screw clamp terminals stranded for output |
| Fixing Mode | By screw M3.5, M3.5 panel Clip-on 35 mm symmetrical rail |
| Shape of Screw Head | Combination roundhead |
| Product Weight | 1.9 oz (55 g) |
| Width | 1.6 in (40 mm) |
| Depth | 2.2 in (57 mm) |

Environment

| | |
|---------------------------------------|-----------------------------|
| Ambient Air Temperature for Storage | -40...221 °F (-40...105 °C) |
| Ambient Air Temperature for Operation | -40...131 °F (-40...55 °C) |
| IP Degree of Protection | IP20 |
| Flame Retardance | UL94-V0 |
| Product Certifications | UL CSA CE |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Ordering and shipping details

| | |
|-------------------|---------------|
| Category | US10CP221127 |
| Discount Schedule | 0CP2 |
| GTIN | 3606480278174 |
| Returnability | No |
| Country of origin | TW |

Packing Units

| | |
|------------------------------|----------------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 3.3 in (8.4 cm) |
| Package 1 Width | 1.6 in (4.0 cm) |
| Package 1 Length | 1.2 in (3.0 cm) |
| Package 1 Weight | 1.9 oz (55.0 g) |
| Unit Type of Package 2 | CAR |
| Number of Units in Package 2 | 10 |
| Package 2 Height | 3.3 in (8.5 cm) |
| Package 2 Width | 2.45 in (6.22 cm) |
| Package 2 Length | 8.0000000000 in (20.32 cm) |
| Package 2 Weight | 24.7 oz (700.5 g) |
| Unit Type of Package 3 | BB1 |
| Number of Units in Package 3 | 100 |
| Package 3 Height | 8.6 in (21.8 cm) |
| Package 3 Width | 12.9 in (32.7 cm) |
| Package 3 Length | 17.3 in (43.9 cm) |
| Package 3 Weight | 35.3 lb(US) (16.0 kg) |

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

Reach Free Of Svhc

Toxic Heavy Metal Free

Mercury Free

Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation

[REACH Declaration](#)

Eu Rohs Directive

Pro-active compliance (Product out of EU RoHS legal scope)

[EU RoHS Declaration](#)

China Rohs Regulation

[China RoHS declaration](#)

Environmental Disclosure

[Product Environmental Profile](#)

Weee

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Circularity Profile

No need of specific recycling operations

California Proposition 65

"WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov"