

# Product data sheet

## Characteristics

# VBDN12

## TeSys Mini-Vario - switch disconnector - 12 A - on door



Product availability: Non-Stock - Not normally stocked in distribution facility

Price\*: 90.00 USD



### Main

Range	TeSys
Product name	TeSys Mini-VARIO
Device short name	VBDN
Product or Component Type	Switch disconnector
Performance level	Standard
Poles description	3P
Contacts type and composition	3 NO
Network type	AC DC
Control Type	Rotary handle
Rotary handle mounting style	Direct
Handle colour	Black
Handle front plate colour	Black
Rotary handle padlocking	1 to 3 padlocks 0.16...0.31 in (4...8 mm)

### Complementary

Marking	0 - 1
Mounting support	Handle door Switch door
Fixing mode	Hole 0.89 in (22.5 mm) handle
[Ue] rated operational voltage	690 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	6 KV
[Ith] conventional free air thermal current	12 A
[Ithe] conventional enclosed thermal current	10 A
[Ie] rated operational current	8.1 A AC-23)400 V

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. \*Prices are indicative. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Rated operational power in W	3 KW 230...240 V AC-23A) 4 KW 400...415 V AC-23A) 5.5 KW 500 V AC-23A) 7.5 KW 690 V AC-23A) 1.5 KW 230...240 V AC-3) 3 KW 400...415 V AC-3) 4 KW 500 V AC-3) 4 KW 690 V AC-3)
Intermittent duty class	30
Making capacity	120 A at 400 V AC-21A 120 A at 400 V AC-22A 120 A at 400 V AC-23A
[Icm] rated short-circuit making capacity	0.5 KA 400 V at Ipeak
[Icw] rated short-time withstand current	140 A 400 V 1 s
Rated conditional short-circuit current	6 KA 400 V 12 A aM 6 KA 400 V 12 A gG
Breaking capacity	120 KA 400 V AC-21A) 120 KA 400 V AC-22A) 120 KA 400 V AC-23A)
Device Composition	Switch Handle
Mechanical durability	50000 Cycles
Electrical durability	30000 Cycles DC-1...5 50000 Cycles AC-21
Suitability for isolation	Yes
Connections - terminals	Power circuit screw clamp terminals 0.01 in <sup>2</sup> (4 mm <sup>2</sup> ) flexible - with cable end Power circuit screw clamp terminals 0.01 in <sup>2</sup> (4 mm <sup>2</sup> ) solid
Tightening torque	Power circuit 6.20 lbf.in (0.7 N.m) screw clamp terminals
Base dimension	60 x 60 mm
Maximum Height	2.36 in (60 mm)
Maximum Width	2.36 in (60 mm)
Net Weight	0.39 Lb(US) (0.177 kg)

## Environment

Standards	IEC 60947-3
Product Certifications	UL GL CCC CSA
Protective treatment	TC
IP degree of protection	IP65
Mechanical robustness	Vibrations 10...150 Hz 5 gn) IEC 60068-2-6 Shocks 11 ms 15 gn) IEC 60068-2-27
Ambient Air Temperature for Operation	-4...122 °F (-20...50 °C)
Fire resistance	1760 °F (960 °C) IEC 60695-2-1

## Ordering and shipping details

Category	21730 - V VARIO SWITCH
Discount Schedule	CP1
GTIN	03389110759853
Nbr. of units in pkg.	1
Package weight(Lbs)	6.28 Oz (178 g)
Returnability	No
Country of origin	CZ

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	3.15 In (8 cm)
Package 1 width	3.35 In (8.5 cm)
Package 1 Length	4.72 In (12 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<input checked="" type="checkbox"/> <a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <input checked="" type="checkbox"/> <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<input checked="" type="checkbox"/> Yes
China RoHS Regulation	<input checked="" type="checkbox"/> <a href="#">China RoHS Declaration</a>
Environmental Disclosure	<input checked="" type="checkbox"/> <a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
PVC free	Yes

## Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**