

Product data sheet

Characteristics

VC4GUN

TeSys Vario enclosed, emergency switch disconnector, 63A, UL/CSA



Product availability: Stock - Normally stocked in distribution facility

Price*: 381.00 USD

Main

Range	TeSys
Product name	TeSys VARIO
Device short name	VC-GUN
Product or Component Type	Enclosed emergency stop switch disconnector
Performance level	High performance
Poles description	3P
Control Type	Rotary handle
Handle colour	Red
Handle front plate colour	Yellow
Rotary handle padlocking	1 to 3 padlocks 0.16...0.31 in (4...8 mm)

Complementary

Marking	0 - 1
[Ue] rated operational voltage	690 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	8 KV
[Ithe] conventional enclosed thermal current	63 A
[Ie] rated operational current	57 A AC-23A)400 V
Rated operational power in W	30 KW 400 V AC-23) 22 KW 400 V AC-3)
Intermittent duty class	30
Making capacity	800 A 400 V AC-21A 800 A 400 V AC-22A 800 A 400 V AC-23A
[Icm] rated short-circuit making capacity	2.1 KA 400 V at Ipeak
[Ithe] conventional enclosed thermal current	63.0 A IEC 690 V 63 A UL 600 V
Rated power in hp	15 Hp 240 V, UL 30 Hp 480 V, UL 40 Hp 600 V, UL
[Icw] rated short-time withstand current	960 A 400 V 1 s
Rated conditional short-circuit current	10 KA 400 V 80 A aM 10 KA 400 V 80 A gG
Breaking capacity	640 A 400 V AC-21A) 640 A 400 V AC-22A) 640 A 400 V AC-23A)
Mechanical durability	30000 Cycles
Electrical durability	30000 Cycles AC-21 30000 Cycles DC-1...5
Environmental characteristic	Standard environment
Suitability for isolation	Yes
Connections - terminals	Screw clamp terminals 0.04 in ² (25 mm ²) solid - with cable end screw clamp terminals 0.02 in ² (16 mm ²) flexible
Tightening torque	35.40 Lbf.in (4 N.m) screw clamp terminals
Fire resistance	1760 °F (960 °C) IEC 60595-2-1
Base dimension	60 x 60 mm

Maximum Height	7.60 In (193 mm)
Maximum Width	6.46 In (164 mm)
Maximum Depth	5.20 In (132 mm)
Net Weight	2.05 Lb(US) (0.93 kg)

Environment

Standards	UL 508 CSA C22.2 No 14 IEC 60947-4-1 IEC 60204
Protective treatment	TC
IP degree of protection	IP65 conforming to IEC 60529
NEMA Degree of Protection	NEMA 12
Mechanical robustness	Vibrations 10...150 Hz 1 gn) IEC 60068-2-6 Shocks 11 ms 30 Gn) IEC 60068-2-27
Ambient Air Temperature for Operation	-4...122 °F (-20...50 °C)

Ordering and shipping details

Category	21730 - V VARIO SWITCH
Discount Schedule	CP1
GTIN	03389119413206
Nbr. of units in pkg.	1
Package weight(Lbs)	2.34 Lb(US) (1.062 kg)
Returnability	Yes
Country of origin	CZ

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	8.27 In (21 cm)
Package 1 width	8.46 In (21.5 cm)
Package 1 Length	8.66 In (22 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty 18 months

Product Life Status : Commercialised