

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 185.00 USD



Main

| | |
|---------------------------|------------------------------------|
| Range | TeSys |
| Product name | TeSys VARIO |
| Device short name | VCCD |
| Product or component type | Emergency stop switch disconnecter |

Complementary

| | |
|--|---|
| Device composition | Switch Shaft extension Handle |
| Mounting support | Handle door Switch symmetrical rail Switch plate |
| Fixing mode | Hole 0.89 in (22.5 mm) handle By clips switch By screws switch |
| Performance level | High performance |
| Poles description | 3P |
| Contacts type and composition | 3 NO |
| [Ue] rated operational voltage | 690 V AC 50/60 Hz |
| Rated operational power in W | 11 KW 690 V AC-23A) 3 KW 230...240 V AC-3) 4 KW 400...415 V AC-3) 5.5 KW 500 V AC-3) 7.5 KW 500 V AC-23A) 7.5 KW 690 V AC-3) 4 KW 230...240 V AC-23A) 5.5 KW 400...415 V AC-23A) |
| [Ie] rated operational current | 11 A AC-23 Ue: 400 V |
| [Ith] conventional free air thermal current | 20 A |
| [Ithe] conventional enclosed thermal current | 16 A |
| Making capacity | 200 A 400 V AC-21A 200 A 400 V AC-22A 200 A 400 V AC-23A |

| | |
|---|---|
| Breaking capacity | 200 A 400 V AC-21A) 200 A 400 V AC-22A) 200 A 400 V AC-23A) |
| Rated conditional short-circuit current | 10 KA 400 V 20 A aM 10 KA 400 V 20 A gG |
| [Icm] rated short-circuit making capacity | 1 KA 400 V at Ipeak |
| [Icw] rated short-time withstand current | 300 A 400 V 1 s |
| [Uimp] rated impulse withstand voltage | 8 KV |
| Suitability for isolation | Yes |
| Network type | DC AC |
| Intermittent duty class | 30 |
| Control type | Rotary handle |
| Rotary handle mounting style | Extended |
| Handle colour | Red |
| Handle front plate colour | Yellow |
| Rotary handle padlocking | 1 to 3 padlocks 0.16...0.31 in (4...8 mm) |
| Marking | 0 - 1 |
| Mechanical durability | 100000 Cycles |
| Electrical durability | 100000 Cycles AC-21 30000 Cycles DC-1...5 |
| Connections - terminals | Power circuit screw clamp terminals 0.02 in ² (10 mm ²) solid Power circuit screw clamp terminals 0.01 in ² (6 mm ²) flexible - with cable end |
| Tightening torque | Power circuit 18.59 lbf.in (2.1 N.m) screw clamp terminals |
| Base dimension | 60 x 60 mm |
| Height | 2.91 In (74 mm) |
| Width | 2.36 In (60 mm) |
| Net weight | 0.86 Lb(US) (0.392 kg) |

Environment

| | |
|---------------------------------------|--|
| Standards | IEC 60947-3 |
| Product certifications | CCC CSA GL UL |
| IP degree of protection | IP20 conforming to IEC 60529 IP65 |
| Protective treatment | TC |
| Mechanical robustness | Vibrations 10...150 Hz 1 gn) IEC 60068-2-6 Shocks 11 ms 30 Gn) IEC 60068-2-27 |
| Ambient air temperature for operation | -4...122 °F (-20...50 °C) |
| Fire resistance | 1760 °F (960 °C) IEC 60695-2-1 |
| Compatibility code | Main switch disconnecter |

Ordering and shipping details

| | |
|-----------------------|------------------------|
| Category | 21730 - V VARIO SWITCH |
| Discount Schedule | CP1 |
| GTIN | 03389110759785 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 12.27 Oz (347.9 g) |
| Returnability | No |
| Country of origin | CZ |

Packing Units

| | |
|------------------------|-------------------|
| Unit Type of Package 1 | PCE |
| Package 1 Height | 2.95 In (7.5 cm) |
| Package 1 width | 3.43 In (8.7 cm) |
| Package 1 Length | 9.92 In (25.2 cm) |

Offer Sustainability

| | |
|-----------------------------|---|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |
| PVC free | Yes |
| Halogen content performance | Halogen free product |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Product Life Status : **Commercialised**