

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 287.00 USD



Main

| | |
|---------------------------|---|
| Range | TeSys |
| Product name | TeSys VARIO |
| Device short name | VCF |
| Product or component type | Enclosed emergency stop switch disconnecter |
| Performance level | High performance |
| Poles description | 3P |
| Control type | Rotary handle |
| Handle colour | Red |
| Handle front plate colour | Yellow |
| Rotary handle padlocking | 1 to 3 padlocks 0.16...0.31 in (4...8 mm) |

Complementary

| | |
|--|---|
| Marking | 0 - 1 |
| [Ue] rated operational voltage | 690 V AC |
| [Uimp] rated impulse withstand voltage | 8 KV |
| [Ithe] conventional enclosed thermal current | 32 A |
| [Ie] rated operational current | 29 A AC-23A)400 V |
| Rated operational power in W | 15 KW 400 V AC-23) 11 KW 400 V AC-3) |
| Intermittent duty class | 30 |
| Making capacity | 400 A 400 V AC-21A 400 A 400 V AC-22A 400 A 400 V AC-23A |
| [Icm] rated short-circuit making capacity | 1 KA 400 V at Ipeak |
| [Icw] rated short-time withstand current | 480 A 400 V 1 s |
| Rated conditional short-circuit current | 10 KA 400 V 50 A aM 10 KA 400 V 50 A gG |
| Breaking capacity | 320 A 400 V AC-21A) 320 A 400 V AC-22A) 320 A 400 V AC-23A) |
| Mechanical durability | 100000 Cycles |

| | |
|------------------------------|---|
| Electrical durability | 100000 Cycles AC-21 30000 Cycles DC-1...5 |
| Environmental characteristic | Standard environment |
| Suitability for isolation | Yes |
| Connections - terminals | Screw clamp terminals 0.02 in ² (10 mm ²) solid screw clamp terminals 0.01 in ² (6 mm ²) flexible - with cable end |
| Tightening torque | 18.59 Lbf.In (2.1 N.m) screw clamp terminals |
| Fire resistance | 1760 °F (960 °C) IEC 60595-2-1 |
| Base dimension | 60 x 60 mm |
| Height | 5.75 In (146 mm) |
| Width | 3.54 In (90 mm) |
| Depth | 5.16 In (131 mm) |
| Net weight | 1.10 Lb(US) (0.5 kg) |

Environment

| | |
|---------------------------------------|--|
| Standards | IEC 60204 IEC 60947-4-1 |
| Protective treatment | TC |
| IP degree of protection | IP65 conforming to IEC 60529 |
| Mechanical robustness | Vibrations 10...150 Hz 1 gn) IEC 60068-2-6 Shocks 11 ms 30 Gn) IEC 60068-2-27 |
| Ambient air temperature for operation | -4...122 °F (-20...50 °C) |

Ordering and shipping details

| | |
|-----------------------|------------------------|
| Category | 21730 - V VARIO SWITCH |
| Discount Schedule | CP1 |
| GTIN | 03389110194104 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 16.68 Oz (473 g) |
| Returnability | No |
| Country of origin | CZ |

Packing Units

| | |
|------------------------------|--------------------------|
| Unit Type of Package 1 | PCE |
| Package 1 Height | 4.45 In (11.3 cm) |
| Package 1 width | 5.71 In (14.5 cm) |
| Package 1 Length | 6.22 In (15.8 cm) |
| Unit Type of Package 2 | S03 |
| Number of Units in Package 2 | 7 |
| Package 2 Weight | 8.33 Lb(US) (3.777 kg) |
| Package 2 Height | 11.81 In (30 cm) |
| Package 2 width | 11.81 In (30 cm) |
| Package 2 Length | 15.75 In (40 cm) |
| Unit Type of Package 3 | P06 |
| Number of Units in Package 3 | 56 |
| Package 3 Weight | 88.72 Lb(US) (40.244 kg) |
| Package 3 Height | 31.50 In (80 cm) |
| Package 3 width | 31.50 In (80 cm) |
| Package 3 Length | 23.62 In (60 cm) |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

| | |
|-----------------------|-----------------------|
| Product Life Status : | Commercialised |
|-----------------------|-----------------------|