

Product data sheet

Characteristics

VCFN12GE

TeSys Vario enclosed, emergency stop switch disconnector, 10A, IP55



Product availability: Stock - Normally stocked in distribution facility

Price*: 179.00 USD



Main

| | |
|---------------------------|---|
| Range | TeSys |
| Product name | TeSys Mini-VARIO |
| Device short name | VCFN |
| Product or Component Type | Emergency stop switch disconnector |
| Performance level | Standard |
| Poles description | 3P |
| Control Type | Rotary handle |
| Handle colour | Red |
| Handle front plate colour | Yellow |
| Rotary handle padlocking | 1 to 3 padlocks 0.16...0.31 in (4...8 mm) |

Complementary

| | |
|--|---|
| Marking | 0 - 1 |
| [Ue] rated operational voltage | 690 V AC |
| [Uimp] rated impulse withstand voltage | 8 KV |
| [Ithe] conventional enclosed thermal current | 10 A |
| [Ie] rated operational current | 8.1 A AC-23A)400 V |
| Rated operational power in W | 4 KW 400 V AC-23) 3 KW 400 V AC-3) |
| Intermittent duty class | 30 |
| Making capacity | 120 A at 400 V AC-21A 120 A at 400 V AC-22A 120 A at 400 V AC-23A |
| [Icm] rated short-circuit making capacity | 0.5 KA 400 V at Ipeak |
| [Icw] rated short-time withstand current | 140 A 400 V 1 s |
| Rated conditional short-circuit current | 6 KA 400 V 12 A aM 6 KA 400 V 12 A gG |
| Breaking capacity | 120 A 400 V AC-22A) 120 A 400 V AC-23A) 120 A AC-21A) |
| Mechanical durability | 50000 Cycles |

| | |
|---------------------------|--|
| Electrical durability | 30000 Cycles DC-1...5 50000 Cycles AC-21 |
| Suitability for isolation | Yes |
| Connections - terminals | Control circuit connector 0.01 in ² (4 mm ²) flexible with cable end Control circuit connector 0.01 in ² (4 mm ²) solid |
| Tightening torque | Control circuit 6.20 lbf.in (0.7 N.m) connector |
| Fire resistance | 1760 °F (960 °C) IEC 60595-2-1 |
| Base dimension | 60 x 60 mm |
| Maximum Height | 5.16 In (131 mm) |
| Maximum Width | 3.25 In (82.5 mm) |
| Maximum Depth | 4.17 In (106 mm) |
| Net Weight | 0.93 Lb(US) (0.422 kg) |

Environment

| | |
|---------------------------------------|--|
| Standards | IEC 60947-4-1 |
| Protective treatment | TC |
| Mechanical robustness | Vibrations 10...150 Hz 1 gn) IEC 60068-2-6 Shocks 11 ms 30 Gn) IEC 60068-2-27 |
| Ambient Air Temperature for Operation | -4...122 °F (-20...50 °C) |

Ordering and shipping details

| | |
|-----------------------|------------------------|
| Category | 21730 - V VARIO SWITCH |
| Discount Schedule | CP1 |
| GTIN | 03389110759983 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 10.72 Oz (304 g) |
| Returnability | Yes |
| Country of origin | CZ |

Packing Units

| | |
|------------------------------|---------------------------|
| Unit Type of Package 1 | PCE |
| Package 1 Height | 3.54 In (9 cm) |
| Package 1 width | 4.33 In (11 cm) |
| Package 1 Length | 5.51 In (14 cm) |
| Unit Type of Package 2 | S02 |
| Number of Units in Package 2 | 7 |
| Package 2 Weight | 5.45 Lb(US) (2.471 kg) |
| Package 2 Height | 5.91 In (15 cm) |
| Package 2 width | 11.81 In (30 cm) |
| Package 2 Length | 15.75 In (40 cm) |
| Unit Type of Package 3 | P06 |
| Number of Units in Package 3 | 112 |
| Package 3 Weight | 110.17 Lb(US) (49.972 kg) |
| Package 3 Height | 31.50 In (80 cm) |
| Package 3 width | 31.50 In (80 cm) |
| Package 3 Length | 23.62 In (60 cm) |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation | <input checked="" type="checkbox"/> REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant <input checked="" type="checkbox"/> EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | <input checked="" type="checkbox"/> Yes |
| China RoHS Regulation | <input checked="" type="checkbox"/> China RoHS Declaration |
| Environmental Disclosure | <input checked="" type="checkbox"/> Product Environmental Profile |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Product Life Status : **Commercialised**