

# Product data sheet

## Characteristics

# VZ16

## TeSys VARIO - additional earthing block - 175 A - for V5 / V6



Product availability: Non-Stock - Not normally stocked in distribution facility

Price\*: 70.00 USD



### Main

Range	TeSys
Device short name	VZ
Product or Component Type	Additional earthing block
Performance level	High performance
Contacts type and composition	Without
Product Compatibility	V5 V6
Network type	AC DC
Network Frequency	50/60 Hz

### Complementary

Mounting Location	Left Right
[Ue] rated operational voltage	690 V AC 50/60 Hz
[Uiimp] rated impulse withstand voltage	6 KV
[Ith] conventional free air thermal current	175 A
Connections - terminals	Screw clamp terminals
Maximum Height	4.92 In (125 mm)
Maximum Width	1.18 In (30 mm)
Maximum Depth	2.48 In (63 mm)
Net Weight	0.55 Lb(US) (0.25 kg)

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. \*Prices are indicative. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Environment

Standards	IEC 60947-3
Product Certifications	GL CSA UL UKCA
Protective treatment	TC
IP degree of protection	IP20 conforming to IEC 60529
Mechanical robustness	Vibrations 10...150 Hz 5 gn) IEC 60068-2-6 Shocks 11 ms 15 gn) IEC 60068-2-27
Ambient Air Temperature for Operation	-4...122 °F (-20...50 °C)
Fire resistance	1760 °F (960 °C) IEC 60695-2-1

## Ordering and shipping details

Category	21730 - V VARIO SWITCH
Discount Schedule	CP1
GTIN	03389110551952
Nbr. of units in pkg.	1
Package weight(Lbs)	8.68 Oz (246 g)
Returnability	No
Country of origin	CZ

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	2.76 In (7 cm)
Package 1 width	5.75 In (14.6 cm)
Package 1 Length	3.39 In (8.6 cm)
Unit Type of Package 2	S03
Number of Units in Package 2	30
Package 2 Weight	17.22 Lb(US) (7.813 kg)
Package 2 Height	11.81 In (30 cm)
Package 2 width	11.81 In (30 cm)
Package 2 Length	15.75 In (40 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 <a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	 <a href="#">Yes</a>
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
Environmental Disclosure	 <a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
PVC free	Yes

## Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**