



Product availability: Non-Stock - Not normally stocked in distribution facility

Price\*: 55.00 USD



### Main

|                               |                                 |
|-------------------------------|---------------------------------|
| Range                         | TeSys                           |
| Device short name             | VZ                              |
| Product or Component Type     | Additional pole                 |
| Performance level             | High performance                |
| Poles description             | 1P                              |
| Contacts type and composition | 1 NO                            |
| Product Compatibility         | V2                              |
| Range compatibility           | TeSys VARIO switch disconnector |
| Network type                  | AC<br>DC                        |
| Network Frequency             | 50/60 Hz                        |
| Suitability for isolation     | Yes                             |

### Complementary

|  |   |
|--|---|
| Mounting Location                            | Right<br>Left   |
| [Ue] rated operational voltage               | 690 V AC 50/60 Hz   |
| [Uimp] rated impulse withstand voltage       | 8 KV  |
| [Ith] conventional free air thermal current  | 40 A  |
| [Ithe] conventional enclosed thermal current | 32 A  |
| Mechanical durability                        | 100000 Cycles   |
| Electrical durability                        | 100000 Cycles AC-21<br>30000 Cycles DC-1...5  |
| Connections - terminals                      | Power circuit screw clamp terminals 0.01 in <sup>2</sup> (6 mm <sup>2</sup> ) flexible - with cable end<br>Power circuit screw clamp terminals 0.02 in <sup>2</sup> (10 mm <sup>2</sup> ) solid |
| Tightening torque                            | Power circuit 18.59 lbf.in (2.1 N.m) screw clamp terminals  |
| Maximum Height                               | 2.91 in (74 mm)   |
| Maximum Width                                | 0.63 in (16 mm)   |
| Maximum Depth                                | 1.38 in (35 mm)   |
| Net Weight                                   | 0.11 Lb(US) (0.05 kg)   |

## Environment

|                                       |  |
|---------------------------------------|--|
| Standards                             | IEC 60947-3  |
| Product Certifications                | CSA<br>GL<br>UL  |
| Protective treatment                  | TC   |
| IP degree of protection               | IP20 conforming to IEC 60529   |
| Mechanical robustness                 | Vibrations 10...150 Hz 1 gn) IEC 60068-2-6<br>Shocks 11 ms 30 Gn) IEC 60068-2-27 |
| Ambient Air Temperature for Operation | -4...122 °F (-20...50 °C)  |
| Fire resistance                       | 1760 °F (960 °C) IEC 60695-2-1   |

## Ordering and shipping details

|                       |                        |
|-----------------------|------------------------|
| Category              | 21730 - V VARIO SWITCH |
| Discount Schedule     | CP1                    |
| GTIN                  | 03389110551877         |
| Nbr. of units in pkg. | 1                      |
| Package weight(Lbs)   | 1.69 Oz (48 g)         |
| Returnability         | No                     |
| Country of origin     | CZ                     |

## Packing Units

|                        |                  |
|------------------------|------------------|
| Unit Type of Package 1 | PCE              |
| Package 1 Height       | 1.46 In (3.7 cm) |
| Package 1 width        | 2.17 In (5.5 cm) |
| Package 1 Length       | 3.54 In (9 cm)   |

## Offer Sustainability

|                             |  |
|-----------------------------|--|
| Sustainable offer status    | Green Premium product  |
| REACH Regulation            | <input checked="" type="checkbox"/> REACH Declaration  |
| REACH free of SVHC          | Yes  |
| EU RoHS Directive           | Compliant <input checked="" type="checkbox"/> EU RoHS Declaration  |
| Toxic heavy metal free      | Yes  |
| Mercury free                | Yes  |
| RoHS exemption information  | <input checked="" type="checkbox"/> Yes  |
| China RoHS Regulation       | <input checked="" type="checkbox"/> China RoHS Declaration   |
| Environmental Disclosure    | <input checked="" type="checkbox"/> Product Environmental Profile  |
| WEEE                        | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |
| PVC free                    | Yes  |
| Halogen content performance | Halogen free product   |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Product Life Status : **Commercialised**