

# Product data sheet

## Characteristics

# VZN11

## TeSys Mini-VARIO - additional neutral block - 20 A - for VN12, VN20



Product availability: Non-Stock - Not normally stocked in distribution facility

Price\*: 29.30 USD



### Main

Range	TeSys
Device short name	VZN
Product or component type	Additional neutral block
Performance level	Standard
Poles description	1N
Contacts type and composition	1 NO
Contact operation	Early make, late break
Product compatibility	VN12 VN20
Network type	AC DC
Network frequency	50/60 Hz
Mounting location	Right

### Complementary

Range compatibility	TeSys VARIO VCFN switch disconnector
[Ue] rated operational voltage	690 V AC 50/60 Hz
[Uiimp] rated impulse withstand voltage	6 KV
[Ith] conventional free air thermal current	20 A
[Ithe] conventional enclosed thermal current	16 A
Mechanical durability	50000 Cycles
Electrical durability	30000 Cycles DC-1...5 50000 Cycles AC-21
Connections - terminals	Screw clamp terminals 0.01 in <sup>2</sup> (4 mm <sup>2</sup> ) flexible - with cable end screw clamp terminals 0.01 in <sup>2</sup> (4 mm <sup>2</sup> ) solid
Tightening torque	6.20 Lbf.In (0.7 N.m) screw clamp terminals
Height	1.79 in (45.5 mm)
Width	0.47 in (12 mm)
Depth	1.54 in (39 mm)
Net Weight	0.04 Lb(US) (0.02 kg)

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. \*Prices are indicative. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Environment

Standards	IEC 60947-3
Product certifications	CSA GL UL
Protective treatment	TC
IP degree of protection	IP20 conforming to IEC 60529
Mechanical robustness	Vibrations 10...150 Hz 1 gn) IEC 60068-2-6 Shocks 11 ms 15 gn) IEC 60068-2-27
Ambient air temperature for operation	-4...122 °F (-20...50 °C)
Fire resistance	1760 °F (960 °C) IEC 60695-2-1

## Ordering and shipping details

Category	21730 - V VARIO SWITCH
Discount Schedule	CP1
GTIN	03389110760019
Nbr. of units in pkg.	1
Package weight(Lbs)	0.78 Oz (22 g)
Returnability	No
Country of origin	CZ

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	1.06 In (2.7 cm)
Package 1 width	2.24 In (5.7 cm)
Package 1 Length	2.95 In (7.5 cm)
Unit Type of Package 2	S01
Number of Units in Package 2	70
Package 2 Weight	3.96 Lb(US) (1.794 kg)
Package 2 Height	5.91 In (15 cm)
Package 2 width	5.91 In (15 cm)
Package 2 Length	15.75 In (40 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 <a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
Environmental Disclosure	 <a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
PVC free	Yes

## Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**