

Product availability: Stock - Normally stocked in distribution facility

Price\*: 72.00 USD



## Main

|                                 |                         |
|---------------------------------|-------------------------|
| Range of product                | Harmony XB5             |
| Product or component type       | Pilot light             |
| Device short name               | XB5                     |
| Bezel material                  | Dark grey plastic       |
| Fixing collar material          | Plastic                 |
| Head type                       | Standard                |
| Mounting diameter               | 0.87 In (22 mm)         |
| Sale per indivisible quantity   | 1                       |
| Shape of signaling unit head    | Round                   |
| Cap/operator or lens colour     | Green                   |
| Operator additional information | With plain lens         |
| Light source                    | Protected LED           |
| Bulb base                       | Integral LED            |
| Light source colour             | Green                   |
| [Us] rated supply voltage       | 110...120 V AC 50/60 Hz |
| Device presentation             | Complete product        |

## Complementary

|  |   |
|--|---|
| Height                                 | 1.65 In (42 mm)   |
| Width                                  | 1.18 In (30 mm)   |
| Depth                                  | 2.13 In (54 mm)   |
| Terminals description ISO n°1          | (X1-X2)PL   |
| Net weight                             | 0.08 Lb(US) (0.038 kg)  |
| Resistance to high pressure washer     | 1015.26 Psi (7000000 Pa) 131 °F (55 °C) 0.1 m   |
| Connections - terminals                | Screw clamp terminals, <= 2 x 1.5 mm <sup>2</sup> with cable end EN/IEC 60947-1<br>Screw clamp terminals, 1 x 0.22...2 x 2.5 mm <sup>2</sup> without cable end EN/IEC 60947-1 |
| [Ui] rated insulation voltage          | 250 V 3)EN 60947-1  |
| [Uimp] rated impulse withstand voltage | 4 KV EN 60947-1   |
| Signalling type                        | Steady  |
| GCR BRIDGE                             | XB5AVCUST04   |

|                       |                                     |
|-----------------------|-------------------------------------|
| Compatibility code    | XB5                                 |
| Supply voltage limits | 100...132 V AC                      |
| Current consumption   | 14 mA                               |
| Service life          | 100000 H at rated voltage and 25 °C |
| Surge withstand       | 1 KV IEC 61000-4-5                  |

## Environment

|                                       |   |
|---------------------------------------|---|
| Protective treatment                  | TH  |
| Ambient air temperature for storage   | -40...158 °F (-40...70 °C)  |
| Ambient air temperature for operation | -40...158 °F (-40...70 °C)  |
| Overvoltage category                  | Class II IEC 60536  |
| IP degree of protection               | IP66 IEC 60529<br>IP67 IEC 60529<br>IP69 IEC 60529<br>IP69K ISO 20653   |
| NEMA degree of protection             | NEMA 13<br>NEMA 4X  |
| IK degree of protection               | IK05 IEC 50102  |
| Product certifications                | CSA<br>UL Listed  |
| Vibration resistance                  | 5 gn 12...500 Hz)IEC 60068-2-6  |
| Shock resistance                      | 50 gn 18 ms) half sine wave acceleration IEC 60068-2-27<br>30 gn 11 ms) half sine wave acceleration IEC 60068-2-27  |
| Resistance to fast transients         | 2 KV IEC 61000-4-4  |
| Resistance to electromagnetic fields  | 9.14 V/M (10 V/m) IEC 61000-4-3   |
| Electromagnetic compatibility         | Electrostatic discharge 6 kV on contact (on metal parts)) IEC 61000-4-2<br>Electrostatic discharge 8 kV in free air (in insulating parts)) IEC 61000-4-2<br>Electromagnetic emissionclass B IEC 55011 |
| Resistance to electrostatic discharge | 6 KV on contact (on metal parts) IEC 61000-4-2<br>8 KV in free air (in insulating parts) IEC 61000-4-2  |
| Electromagnetic emission              | Class B IEC 55011   |

## Ordering and shipping details

|                       |                                       |
|-----------------------|---------------------------------------|
| Category              | 22467 - PUSHBUTTONS,22MM(PLASTIC) NEW |
| Discount Schedule     | CS2                                   |
| GTIN                  | 03389110903812                        |
| Nbr. of units in pkg. | 1                                     |
| Package weight(Lbs)   | 1.23 Oz (35 g)                        |
| Returnability         | Yes                                   |
| Country of origin     | FR                                    |

## Packing Units

|                              |                    |
|------------------------------|--------------------|
| Unit Type of Package 1       | PCE                |
| Package 1 Height             | 1.34 In (3.4 cm)   |
| Package 1 width              | 2.13 In (5.4 cm)   |
| Package 1 Length             | 3.46 In (8.8 cm)   |
| Unit Type of Package 2       | BB1                |
| Number of Units in Package 2 | 5                  |
| Package 2 Weight             | 6.42 Oz (182 g)    |
| Package 2 Height             | 1.34 In (3.4 cm)   |
| Package 2 width              | 2.13 In (5.4 cm)   |
| Package 2 Length             | 10.43 In (26.5 cm) |
| Unit Type of Package 3       | S02                |
| Number of Units in Package 3 | 50                 |

|                  |                        |
|------------------|------------------------|
| Package 3 Weight | 4.75 Lb(US) (2.154 kg) |
| Package 3 Height | 5.91 In (15 cm)        |
| Package 3 width  | 11.81 In (30 cm)       |
| Package 3 Length | 15.75 In (40 cm)       |

### Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| California proposition 65  | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation           | <a href="#">REACH Declaration</a>   |
| REACH free of SVHC         | Yes   |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>  |
| Mercury free               | Yes   |
| RoHS exemption information | <a href="#">Yes</a>   |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>  |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>   |
| Circularity Profile        | <a href="#">End Of Life Information</a>   |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.  |


### Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

---

Dimensions

---



e: clamping thickness: 1 to 6 mm / 0.04 to 0.24 in.

b: 30 mm / 1.18 in.

c: 41.5 mm / 1.63 in.

Panel Cut-out for Pushbuttons, Switches and Pilot Lights (Finished Holes, Ready for Installation)


Connection by Screw Clamp Terminals or Plug-in Connectors or on Printed Circuit Board



- (1) Diameter on finished panel or support
- (2) For selector switches and Emergency stop buttons, use of an anti-rotation plate type ZB5AZ902 is recommended.
- (3)  $\varnothing 22.5$  mm recommended ( $\varnothing 22.3 \text{ }_0^{+0.4}$ ) /  $\varnothing 0.89$  in. recommended ( $\varnothing 0.88 \text{ in. }_0^{+0.016}$ )

| Connections                                   | a in mm | a in in. | b in mm | b in in. |
|---|---------|----------|---------|----------|
| By screw clamp terminals or plug-in connector | 40      | 1.57     | 30      | 1.18     |
| By Faston connectors                          | 45      | 1.77     | 32      | 1.26     |
| On printed circuit board                      | 30      | 1.18     | 30      | 1.18     |

Detail of Lug Recess



- (1) Diameter on finished panel or support
- (2) For selector switches and Emergency stop buttons, use of an anti-rotation plate type ZB5AZ902 is recommended.
- (3)  $\varnothing 22.5$  mm recommended ( $\varnothing 22.3 \text{ }_0^{+0.4}$ ) /  $\varnothing 0.89$  in. recommended ( $\varnothing 0.88 \text{ in. }_0^{+0.016}$ )

Product Life Status : **Commercialised**