

# Product data sheet

## Characteristics

# XCSDMC5902

Coded magnetic switch, Telemecanique

Safety switches XCS, XCSDMC, 1 NC + 1 NO,  
staggered, 2 m

Product availability: Stock - Normally stocked in distribution facility

Price\*: 89.00 USD



## Main

|                                |                                   |
|--------------------------------|-----------------------------------|
| Range of product               | Telemecanique Safety switches XCS |
| Product or component type      | Coded magnetic switch             |
| Component name                 | XCSDMC                            |
| Design                         | Rectangular, compact              |
| Size                           | 51 x 16 x 7 mm                    |
| Contacts type and composition  | 1 NC + 1 NO                       |
| Contact operation              | Staggered                         |
| Material                       | Plastic                           |
| Electrical connection          | Pre-cabled                        |
| Cable composition              | 4 x 0.25 mm <sup>2</sup>          |
| Cable length                   | 6.56 Ft (2 m)                     |
| Number of poles                | 2                                 |
| Approach directions            | 3 directions                      |
| [Ue] rated operational voltage | 24 V DC                           |
| [Ui] rated insulation voltage  | 100 V DC                          |

## Complementary

|                                        |                                        |
|----------------------------------------|----------------------------------------|
| [Sa] assured operating distance        | 0.20 ln (5 mm)                         |
| [Sar] assured tripping distance        | 0.59 ln (15 mm)                        |
| Maximum [le] rated operational current | 100 MA                                 |
| [Uimp] rated impulse withstand voltage | 2.5 KV EN/IEC 60947-5-1                |
| Resistance across terminals            | 10 Ohm                                 |
| Short-circuit protection               | 500 MA external cartridge fuse gG (gl) |
| Contacts material                      | Rhodium                                |
| Electrical durability                  | 1200000 Cycles                         |
| Maximum switching voltage              | 100 V DC                               |
| Switching capacity in mA               | 0.1...100 mA                           |
| Insulation resistance                  | 1000 MOhm                              |
| Breaking capacity                      | 10 VA                                  |

|                         |                                                                                                                                                                                                                                                                                         |
|-------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Switching frequency     | 150 Hz                                                                                                                                                                                                                                                                                  |
| Safety level            | Can reach category 4 with the appropriate monitoring system and correctly-wired EN/ISO 13849-1<br>Can reach PL = e with the appropriate monitoring system and correctly-wired EN/ISO 13849-1<br>Can reach SIL 3 with the appropriate monitoring system and correctly-wired EN/IEC 61508 |
| Safety reliability data | B10d = 50000000 value given for a life time of 20 years limited by mechanical or contact wear                                                                                                                                                                                           |
| Enclosure material      | Thermoplastic PBT                                                                                                                                                                                                                                                                       |
| Cable material          | PVC                                                                                                                                                                                                                                                                                     |
| Depth                   | 0.28 in (7 mm)                                                                                                                                                                                                                                                                          |
| Height                  | 2.01 in (51 mm)                                                                                                                                                                                                                                                                         |
| Width                   | 0.63 in (16 mm)                                                                                                                                                                                                                                                                         |
| Net weight              | 0.22 Lb(US) (0.101 kg)                                                                                                                                                                                                                                                                  |

## Environment

|                                        |                                                                                              |
|----------------------------------------|----------------------------------------------------------------------------------------------|
| Standards                              | ISO 14119<br>CSA C22.2 No 14<br>EN/IEC 60947-5-1<br>EN/ISO 12100<br>UL 508<br>EN/IEC 60204-1 |
| Product certifications                 | UL<br>CSA<br>BG                                                                              |
| Protective treatment                   | TH                                                                                           |
| Ambient air temperature for operation  | -13...185 °F (-25...85 °C)                                                                   |
| Ambient air temperature for storage    | -40...185 °F (-40...85 °C)                                                                   |
| Vibration resistance                   | 10 gn 10...150 Hz IEC 60068-2-6                                                              |
| Shock resistance                       | 30 gn 11 ms IEC 60068-2-27                                                                   |
| Maximum sensitivity to magnetic fields | 0.3 MT                                                                                       |
| Electrical shock protection class      | Class II EN/IEC 61140                                                                        |
| IP degree of protection                | IP66 conforming to IEC 60529<br>IP67 conforming to IEC 60529                                 |

## Ordering and shipping details

|                       |                                 |
|-----------------------|---------------------------------|
| Category              | 22411 - LIMIT SWITCHES,IEC,XCKJ |
| Discount Schedule     | T                               |
| GTIN                  | 03389110971682                  |
| Nbr. of units in pkg. | 1                               |
| Package weight(Lbs)   | 3.67 Oz (104 g)                 |
| Returnability         | Yes                             |
| Country of origin     | FR                              |

## Packing Units

|                              |                       |
|------------------------------|-----------------------|
| Unit Type of Package 1       | PCE                   |
| Package 1 Height             | 1.50 in (3.8 cm)      |
| Package 1 width              | 5.31 in (13.5 cm)     |
| Package 1 Length             | 5.91 in (15 cm)       |
| Unit Type of Package 2       | S02                   |
| Number of Units in Package 2 | 20                    |
| Package 2 Weight             | 5.36 Lb(US) (2.43 kg) |
| Package 2 Height             | 5.91 in (15 cm)       |
| Package 2 width              | 11.81 in (30 cm)      |
| Package 2 Length             | 15.75 in (40 cm)      |

|                              |                          |
|------------------------------|--------------------------|
| Unit Type of Package 3       | P06                      |
| Number of Units in Package 3 | 320                      |
| Package 3 Weight             | 111.69 Lb(US) (50.66 kg) |
| Package 3 Height             | 31.50 In (80 cm)         |
| Package 3 width              | 31.50 In (80 cm)         |
| Package 3 Length             | 23.62 In (60 cm)         |

### Offer Sustainability

|                            |                                                                                                                                                                                                                                                                                                                                                                                   |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| California proposition 65  | WARNING: This product can expose you to chemicals including: Diisobutyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isooctyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation           | <input checked="" type="checkbox"/> <a href="#">REACH Declaration</a>                                                                                                                                                                                                                                                                                                             |
| REACH free of SVHC         | Yes                                                                                                                                                                                                                                                                                                                                                                               |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <input checked="" type="checkbox"/> <a href="#">EU RoHS Declaration</a>                                                                                                                                                                                                                                                |
| Toxic heavy metal free     | Yes                                                                                                                                                                                                                                                                                                                                                                               |
| Mercury free               | Yes                                                                                                                                                                                                                                                                                                                                                                               |
| RoHS exemption information | <input checked="" type="checkbox"/> Yes                                                                                                                                                                                                                                                                                                                                           |

### Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Product Life Status : **Commercialised**