

# Product data sheet

## Characteristics

# XUAH0224

Photoelectric sensors XU, XUA, thru beam, Sn 2 m, 12...24 VDC, cable 2 m

Product availability: Non-Stock - Not normally stocked in distribution facility

Price\*: 125.00 USD



### Main

Range of Product	Telemecanique Photoelectric sensors XU
Series name	Application assembly
Electronic sensor type	Photo-electric sensor
Sensor name	XUA
Sensor design	Cylindrical M8
Detection system	Thru beam
Material	Metal
Line of sight type	Axial
Type of output signal	Discrete
Supply circuit type	DC
Wiring Technique	3-wire
Discrete output type	PNP
Discrete output function	1 NC
Electrical connection	Cable
Cable length	6.56 Ft (2 m)
Product Specific Application	-
Emission	Infrared thru beam
[Sn] nominal sensing distance	6.56 Ft (2 m) thru beam need a transmitter XUAH0203

### Complementary

Enclosure Material	Nickel Plated Brass
Lens material	PMMA
Maximum sensing distance	13.12 Ft (4 m)
Output Type	Solid state
Add on output	Without
Cable composition	3 x 0.14 mm <sup>2</sup>
Wire insulation material	PvR
Cable outer diameter	0.14 In (3.5 mm)
Status LED	1 LED yellow)output state
[Us] rated supply voltage	12...24 V DC with reverse polarity protection
Supply voltage limits	10...30 V DC

Switching capacity in mA	<= 100 mA overload and short-circuit protection)
Switching frequency	<= 2000 Hz
Maximum voltage drop	<1 V closed state)
Current consumption	<= 10 mA no-load
Maximum delay first up	20 Ms
Maximum delay response	0.25 Ms
Maximum delay recovery	0.25 Ms
Setting-up	Without sensitivity adjustment
Diameter	0.31 In (8 mm)
Length	1.89 In (48 mm)
Net Weight	0.11 Lb(US) (0.05 kg)

## Environment

Product Certifications	CE CULus
Ambient air temperature for operation	-13...131 °F (-25...55 °C)
Ambient Air Temperature for Storage	-22...158 °F (-30...70 °C)
Vibration resistance	7 gn +/- 1 mm 10...55 Hz) IEC 60068-2-6
Shock resistance	30 gn 11 ms) IEC 60068-2-27
IP degree of protection	IP67 conforming to IEC 60529 IP65 IEC 60529

## Ordering and shipping details

Category	22481 - SENSORS, PHOTOELECTRIC
Discount Schedule	DS2
GTIN	03389110427219
Nbr. of units in pkg.	1
Package weight(Lbs)	1.87 Oz (53 g)
Returnability	No
Country of origin	FR

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	2.56 In (6.5 cm)
Package 1 width	1.65 In (4.2 cm)
Package 1 Length	3.78 In (9.6 cm)
Unit Type of Package 2	S01
Number of Units in Package 2	24
Package 2 Weight	3.30 Lb(US) (1.497 kg)
Package 2 Height	5.91 In (15 cm)
Package 2 width	5.91 In (15 cm)
Package 2 Length	15.75 In (40 cm)

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Diisodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>


## Contractual warranty

---

Warranty	18 months
----------	-----------

---

Dimensions



(1) LED, 4 viewing ports at 90°


Note Fixing nut tightening torque : <2N.m

---

Wiring Schemes


---

PNP




BN : Brown  
BU : Blue  
BK : Black

Detection Curves



Excess Gain Curves (Ambient temperature:  $\pm 25 \text{ }^\circ\text{C}$ )



(Y) Gain  
(X) Distance (m)

Product Life Status : **Commercialised**