

Product data sheet

Characteristics

XVR13B04L

Harmony XVR, Rotating beacon, Ø130, red, without buzzer, 24 V AC/DC



Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 172.50 USD



Main

Range of product	Harmony XVR
Product or Component Type	Prewired rotating mirror beacon
Sound signalling	Without
Device short name	XVR
Mounting diameter	5.12 In (130 mm)
IP degree of protection	IP66 IEC 60529 IP67 IEC 60529
[Us] rated supply voltage	24 V AC/DC
Light source	High luminosity LED, red

Complementary

Material	ABS (acrylonitrile butadiene-styrene) body part PC globe
CAD overall width	5.12 In (130 mm)
CAD overall depth	5.12 In (130 mm)
Product Weight	1.81 Lb(US) (0.82 kg)
Marking	CE
Product mounting	By 3 M6 screws
[Uimp] rated impulse withstand voltage	0.8 KV
Current Consumption	125 mA
Flashing frequency	2.7 Hz
Clamping Connection Capacity	1.25 mm ²
AWG gauge	AWG 18
Cable length	15.75 In (400 mm)

Environment

Standards	EN/IEC 61000-6-2 EN/IEC 61000-6-4
Protective treatment	TC
Ambient Air Temperature for Storage	-31...158 °F (-35...70 °C)
Ambient Air Temperature for Operation	-22...122 °F (-30...50 °C)
Electrical shock protection class	Class II IEC 61140

Ordering and shipping details

Category	22617 - XVC TOWER LIGHTS
Discount Schedule	XV
GTIN	3389119045285
Nbr. of units in pkg.	1
Package weight(Lbs)	5.50 Lb(US) (2.494 kg)
Returnability	No
Country of origin	ID

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	10.43 In (26.5 cm)
Package 1 width	7.36 In (18.7 cm)
Package 1 Length	7.40 In (18.8 cm)
Unit Type of Package 2	S04
Number of Units in Package 2	6
Package 2 Weight	17.63 Lb(US) (7.996 kg)
Package 2 Height	11.81 In (30 cm)
Package 2 width	15.75 In (40 cm)
Package 2 Length	23.62 In (60 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information



Contractual warranty

Warranty	18 months
----------	-----------

Rotating Mirror Beacon


Dimensions

mm
in.



Rotating Mirror Beacon

Panel Cut-out



Product Life Status : Commercialised