

# Product data sheet

## Characteristics

# XXR18A4KAM12

Ultrasonic sensors XX, ultrasonic sensor cylindrical M18, receiver, Sn 1 m -2 NO, M12 connector



Product availability: Non-Stock - Not normally stocked in distribution facility

Price\*: 278.00 USD



### Main

Range of Product	Telemecanique Ultrasonic sensors XX
Sensor Type	Ultrasonic sensor receiver
Series name	General purpose
Sensor name	XXR
Sensor design	Cylindrical M18
Detection system	Thru beam need a transmitter XXT18A4M12)
[Sn] nominal sensing distance	3.28 Ft (1 m) fixed
Material	Plastic
Type of output signal	Discrete
Discrete output function	2 NO
Wiring Technique	4-wire
Discrete output type	PNP and NPN
[Us] rated supply voltage	12...24 V DC reverse polarity protection
Electrical connection	Male connector M12 4 pins
[Sd] sensing range	0.00...3.28 Ft (0...1 m)
IP degree of protection	IP67 conforming to IEC 60529

### Complementary

Enclosure Material	ULTEM
Front material	Silicone
Thread type	M18 x 1
Supply voltage limits	10...28 V DC
[Sa] assured operating distance	0.00...3.28 Ft (0...1 m)
Current Consumption	40 mA
Maximum switching current	100 mA overload and short-circuit protection
Maximum voltage drop	1 V
Switching frequency	<= 40 Hz
Maximum delay first up	100 Ms

Maximum delay response	10 Ms
Maximum delay recovery	10 Ms
Marking	CE
Threaded length	2.01 In (51 mm)
Maximum Height	0.71 In (18 mm)
Maximum Width	0.71 In (18 mm)
Maximum Depth	2.56 In (65 mm)
Net Weight	0.07 Lb(US) (0.033 kg)

## Environment

Standards	IEC 60947-5-2
Product Certifications	UL
Ambient Air Temperature for Operation	32...140 °F (0...60 °C)
Ambient Air Temperature for Storage	-40...176 °F (-40...80 °C)
Vibration resistance	+/-1 mm 10...55 Hz)IEC 60068-2-6
Shock resistance	30 gn in all 3 axes 11 ms IEC 60068-2-27
Resistance to electrostatic discharge	8 KV level 4 IEC 61000-4-2
Resistance to electromagnetic fields	9.14 V/M (10 V/m) level 3 IEC 61000-4-3
Resistance to fast transients	1 KV level 3 IEC 61000-4-4

## Ordering and shipping details

Category	22490 - SENSORS-ULTRASONIC (XX5,6)
Discount Schedule	DS2
GTIN	03389119127844
Nbr. of units in pkg.	1
Package weight(Lbs)	1.80 Oz (50.984 g)
Returnability	No
Country of origin	US

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	1.61 In (4.1 cm)
Package 1 width	2.56 In (6.5 cm)
Package 1 Length	3.74 In (9.5 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisobutyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	 <a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	 <a href="#">Yes</a>
Environmental Disclosure	 <a href="#">Product Environmental Profile</a>
Circularity Profile	 <a href="#">End Of Life Information</a>

**Contractual warranty**

Warranty 18 months

**Product Life Status :** Commercialised