

Product data sheet

Characteristics

XXV18B1NAM12

Ultrasonic sensors XX, ultrasonic sensor, M18 metal, Sn 50 mm, NPN NO, M12



Product availability: Stock - Normally stocked in distribution facility

Price*: 98.00 USD



Main

Range of Product	Telemecanique Ultrasonic sensors XX
Sensor Type	Ultrasonic sensor
Series name	General purpose
Sensor name	XXV
Sensor design	Cylindrical M18
Detection system	Diffuse
[Sn] nominal sensing distance	0.16 Ft (0.05 m) fixed
Material	Metal
Type of output signal	Discrete
Discrete output function	1 NO
Wiring Technique	3-wire
Discrete output type	NPN
[Us] rated supply voltage	12...24 V DC reverse polarity protection
Electrical connection	Male connector M12 4 pins
[Sd] sensing range	0.01...0.16 Ft (0.003...0.05 m)
Beam angle	10 °
IP degree of protection	IP67 conforming to IEC 60529

Complementary

Enclosure Material	Brass
Front material	Epoxy
Thread type	M18 x 1
Supply voltage limits	10...36 V DC
[Sa] assured operating distance	0.01...0.16 Ft (0.003...0.05 m)
Maximum differential travel	0.12 In (3 mm)
Blind zone	0.00...0.12 In (0...3 mm)
Transmission frequency	360 KHz
Repeat accuracy	1.5 %
Deviation angle from 90° of object to be detected	-8...8 °

Minimum size of detected object	Cylinder diameter 2 mm 0.07 ft (0.02 m)
Status LED	Output state 1 LED yellow)
Current Consumption	15 mA
Maximum switching current	200 MA overload and short-circuit protection
Maximum voltage drop	2 V
Switching frequency	<= 80 Hz
Maximum delay first up	5 Ms
Maximum delay response	4 Ms
Maximum delay recovery	4 Ms
Marking	CE
Threaded length	2.01 In (51 mm)
Maximum Height	0.71 In (18 mm)
Maximum Width	0.71 In (18 mm)
Maximum Depth	2.95 In (75 mm)
Net Weight	0.11 Lb(US) (0.05 kg)

Environment

Standards	IEC 60947-5-2
Product Certifications	CULus
Ambient Air Temperature for Operation	32...140 °F (0...60 °C)
Ambient Air Temperature for Storage	-40...176 °F (-40...80 °C)
Vibration resistance	+/- 2 mm 10...55 Hz)IEC 60068-2-6
Shock resistance	50 gn in all 3 axes 11 ms IEC 60068-2-27
Resistance to electrostatic discharge	8 KV level 4 IEC 61000-4-2
Resistance to electromagnetic fields	9.14 V/M (10 V/m) level 3 IEC 61000-4-3
Resistance to fast transients	1 KV level 3 IEC 61000-4-4

Ordering and shipping details

Category	22490 - SENSORS-ULTRASONIC (XX5,6)
Discount Schedule	DS2
GTIN	00785901453420
Nbr. of units in pkg.	1
Package weight(Lbs)	2.56 Oz (72.575 g)
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	1.70 In (4.318 cm)
Package 1 width	2.60 In (6.604 cm)
Package 1 Length	3.80 In (9.652 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	 REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Mercury free	Yes

RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status :	Commercialised
-----------------------	----------------