

Product data sheet


Characteristics

XY2CE1C250H7TK

Latching emergency stop rope pull switch,
Telemecanique rope pull switches XY2C, CABLE
300 V AC, 10 A, red RAL 3000

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 536.00 USD



Main

Range of product	Telemecanique Emergency stop rope pull switches XY2C
Product or Component Type	Latching emergency stop rope pull switch
Device short name	XY2CE

Complementary

Number of cables	1
Body Material	Zamak
Cover Material	Stainless steel
Reset	By key-release push-button
Trigger cable anchor point	RH side
Tightening torque	7.08...10.62 Lbf.in (0.8...1.2 N.m)
Marking	CE
Mechanical durability	60000 Cycles
Distance between cable supports	16.40 Ft (5 m)
[Ithe] conventional enclosed thermal current	10 A
Terminals description ISO n°1	(11-22)NC (21-22)NC
Product Weight	3.24 Lb(US) (1.47 kg)
Compatibility code	XY2CE

Environment

Standards	EN/IEC 60947-5-1 Work equipment directive 2009/104/EC EN/IEC 60947-5-5 CSA C22.2 No 14 EN/ISO 13850 UL 508 EN/IEC 60204-1 Machinery directive 2006/42/EC
Protective treatment	TC
Ambient Air Temperature for Operation	-40...158 °F (-40...70 °C)
Ambient Air Temperature for Storage	-40...158 °F (-40...70 °C)

Ordering and shipping details

Category	22441 - LIMIT SWITCHES,CABLE PULL
Discount Schedule	T
GTIN	3389119086189
Nbr. of units in pkg.	1
Package weight(Lbs)	3.31 Lb(US) (1.5 kg)
Returnability	No
Country of origin	MA

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	3.23 In (8.2 cm)
Package 1 width	7.72 In (19.6 cm)
Package 1 Length	5.83 In (14.8 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Diisodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**