

Product data sheet

Characteristics

XY2CH14270TK

Telemecanique emergency stop rope pull switches XY2C, rope pull switch XY2CH, 240 V, AC, 10 A, XY2C

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 480.00 USD



Main

Range of product	Telemecanique Emergency stop rope pull switches XY2C
Device short name	XY2CH

Complementary

Tightening torque	7.08...10.62 Lbf.In (0.8...1.2 N.m)
Marking	CE
Mechanical durability	800000 Cycles
[I]t[he] conventional enclosed thermal current	10 A
Compatibility code	XY2CH

Environment

Protective treatment	TC
Ambient Air Temperature for Operation	-40...158 °F (-40...70 °C)
Ambient Air Temperature for Storage	-40...158 °F (-40...70 °C)

Ordering and shipping details

Category	22441 - LIMIT SWITCHES,CABLE PULL
Discount Schedule	T
GTIN	3389119085717
Nbr. of units in pkg.	1
Package weight(Lbs)	2.31 Lb(US) (1.05 kg)
Returnability	No
Country of origin	MA

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	3.58 In (9.1 cm)
Package 1 width	3.15 In (8 cm)
Package 1 Length	7.68 In (19.5 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisobutyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	 REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**