

Product data sheet


Characteristics

XZCE11P124M

adaptor, plastic - tapped hole Pg 11 - for male connector, M12, 4-wire

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 25.50 USD



Main

Commercial Status	Commercialised
Accessory / separate part designation	4-wire connector adaptor
Accessory / separate part category	Cabling accessories
Accessory / separate part type	Connector adaptor
Cable composition	4 x 0.34 mm ²
Thread type	Pg 11
[In] rated current	4 A

Complementary

Cable length	3.94 in (100 mm)
Total number of wires	4
Electrical connection	1 male connector M12 5 straight
Cable connector fixing	Screw-on
Body material	Plastic
Insulation resistance	> 1000000000 Ohm
Resistance across terminals	<= 5000 mOhm
[Ue] rated operational voltage	300 V DC 250 V AC
Product weight	0.04 lb(US) (0.02 kg)

Environment

IP degree of protection	IP67
Ambient air temperature for operation	-13...176 °F (-25...80 °C)

Ordering and shipping details

Category	22483 - MACHINE CABLES
Discount Schedule	DS3
GTIN	00785901681946
Nbr. of units in pkg.	1
Package weight(Lbs)	0.02
Product availability	Non-Stock - Not normally stocked in distribution facility
Returnability	N
Country of origin	DE

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Compliant - since 0545 - Schneider Electric declaration of conformity

Contractual warranty

Period	18 months
--------	-----------
