

Product data sheet

Characteristics

XZCPV1164L10

Pre wired connectors XZ, straight female, M12, 5 pins, cable PVC 10 m

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 29.00 USD



Main

Range of product	Telemecanique Cabling components
Accessory / separate part category	Cabling accessory
Accessory / separate part type	Pre-wired connectors
Series name	General purpose

Complementary

Electrical connection	Straight female connector M12, 5 pins
Cable connector fixing	Screw-on
Collar material	Metal
Status LED	Without
Cable length	32.81 Ft (10 m)
Cable outer diameter	0.18 In (4.6 mm)
Cable composition	5 x 0.25 mm ²
Wire insulation material	PVC
[Ue] rated operational voltage	60 V AC 75 V DC
Line Rated Current	3 A
Contact resistance	5000 MOhm
Minimum insulating resistance	1 GΩ
Net weight	0.79 Lb(US) (0.36 kg)

Environment

IP degree of protection	IP65 IP67
Product certifications	CULus
Ambient air temperature for operation	-13...176 °F (-25...80 °C) static
Ambient air temperature for storage	-13...176 °F (-25...80 °C)

Ordering and shipping details

Category	22499 - SENSORS ACCESSORIES
Discount Schedule	DS2
GTIN	03389119073219
Nbr. of units in pkg.	1
Package weight(Lbs)	0.9 Lb(US) (0.41 kg)
Returnability	No
Country of origin	PL

Packing Units

Package 1 Height	0.400 Dm
Package 1 width	2.400 Dm
Package 1 Length	3.000 Dm


Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Diisodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes

Contractual warranty

Warranty	18 months
----------	-----------


Dimensions



L : Length of cable

Connections and Schemes

Connectors



BU : Blue
BN : Brown
BK : Black
Y/G : Yellow / Green
BK/WH : Black / White

Product Life Status :	Commercialised
-----------------------	----------------