

3 and 4-Wire 7/8" *minifast*® Cordsets, Standard

- Straight Female Connectors
- NEMA 1, 3, 4, 6P
- IEC IP 67 Protection
- 300 V, 9 A



| Housing Style | Part Number | Cable | Features | Pinout |
|---------------|----------------|---|--|-----------------------------|
| | RKM 31-*M/S816 | AWM PVC Yellow 3x20 AWG 105°C 5.2 mm OD Cable #RF50674-*M† | <i>flexlife</i> | 1. BK 2. BN 3. BU |
| | RKM 40-*M | AWM PVC Yellow 4x18 AWG 105°C 7.3 mm OD Cable #RF50548-*M† | <i>flexlife</i> ® | |
| | RKM 40-*M/S90 | AWM PUR Yellow 4x18 AWG 105°C 7.3 mm OD Cable #RF50544-*M† | <i>Cut/Abrasion Immune</i> | |
| | RKM 40-*M/S101 | AWM TPE Yellow 4x18 AWG 105°C 7.2 mm OD Cable #RF50968-*M† | <i>flexlife-10, High Flex - Over 10 million cycles</i> | |
| | RKM 40-*M/S529 | PUR Yellow 4x20 AWG 105°C 5.7 mm OD Cable #RF50526-*M† | <i>Cut/Abrasion Immune, Braided Mechanical Shield</i> | |
| | RKM 40-*M/S600 | SJOOW CPE Yellow 4x18 AWG 105°C 8.5 mm OD Cable #RF50644-*M† | <i>Weld Flash Immune, Flame Immune</i> | |
| | RKM 40-*M/S824 | ITC PLTC PVC Yellow 4x18 AWG 105°C 7.2 mm OD Cable #RF50844-*M† | <i>flexlife</i> | |

Cordsets

* Length in Meters. Standard cable lengths are 2, 4, 5, 6, 8 and 10 meters. Consult factory for other lengths.
 ** Standard coupling nut material is nickel plated brass "RKM .."; "RK .." indicates nylon, "RKV .." indicates 316 stainless steel, and "RKH .." indicates 316 stainless steel hex.
 † See Section N for *reelfast*® cable information.

5-Wire 7/8" *minifast*® Cordsets, Standard

- Straight Female Connectors
- NEMA 1, 3, 4, 6P
- IEC IP 67 Protection
- 300 V, 9 A



| Housing Style | Part Number | Cable | Features | Pinout | |
|--|-----------------|--|--|--------|---|
| <p>RKM ..**</p> <p>RKVH ..**</p> | RKM 50-*M | AWM PVC Yellow 5x18 AWG 105°C 7.3 mm OD Cable #RF50549-*M [†] | <i>flexlife</i> ® | | |
| | RKM 50-*M/S90 | AWM PUR Yellow 5x18 AWG 105°C 7.3 mm OD Cable #RF50751-*M [†] | <i>Cut/Abrasion Immune</i> | | 1. BK 2. BU 3. GN/YE 4. BN 5. WH |
| | RKM 50-*M/S101 | AWM TPE Yellow 5x18 AWG 105°C 7.2 mm OD Cable #RF51174-*M [†] | <i>flexlife-10, high flex over 10 million cycles</i> | | |
| | RKM 50-*M/S1551 | AWM PVC Yellow 5x18 AWG 105°C 7.3 mm OD Cable #RF50578-*M [†] | <i>Yellow conductor instead of Green/Yellow</i> | | 1. BK 2. BU 3. YE 4. BN 5. WH |
| | RKM 511-*M | AWM PVC Yellow 5x18 AWG 105°C 7.3 mm OD Cable #RF50521-*M [†] | <i>flexlife</i> | | 1. RD/WH 2. RD/BU 3. GN 4. RD/OG 5. RD/BK |
| | RKM 511-*M/S600 | SJOOW CPE Yellow 5x18 AWG 105°C 9.2 mm OD Cable #RF50659-*M [†] | <i>Weld Flash Immune, Flame Immune</i> | | |

* Length in Meters. Standard cable lengths are 2, 4, 5, 6, 8 and 10 meters. Consult factory for other lengths.

** Standard coupling nut material is nickel plated brass "RKM .."; "RK .." indicates nylon, "RKV .." indicates 316 stainless steel, and "RKVH .." indicates 316 stainless steel hex.

[†] See Section N for *reelfast*® cable information.