


6-Wire 7/8" minifast® Cordsets, Standard

- Straight Female Connectors
- NEMA 1, 3, 4, 6P
- IEC IP 67 Protection
- 300 V, 9 A



Housing Style	Part Number	Cable	Features	Pinout
RKM ..** RKVH ..**	RKM 60-*M/S90/S853	AWM PUR Yellow 3x18 AWG 105°C 7.3 mm OD Cable #RF50545-*M [†]	6-pin style connector with 3 conductor	1. BN 2. N/C 3. GN/YE 4. N/C 5. BU 6. N/C
	RKM 61-*M	AWM PVC Yellow 6x18 AWG 105°C 7.3 mm OD Cable #RF50575-*M [†]	flexlife®	1. GN 2. WH 3. BU 4. Gy 5. YE 6. BN
	RKM 61-*M/S739	ITC PLTC PVC Yellow 7x18 AWG 105°C 7.3 mm OD Cable #RF50637-*M [†]	Shielded cable with drain wire, not connected at plug.	
	RKM 61-*M/S763	AWM PVC Black 6x18 AWG 105°C 7.3 mm OD Cable #RF50551-*M [†]	Shielded cable with drain wire, not connected at plug	1. BU 2. WH 3. BK 4. GN 5. RD 6. OG
	RKM 61-*M/S1052/S1587	AWM TPE Grey 6x18 AWG 105°C 7.2 mm OD Cable #RF51274-*M [†]	weldlife, Weld Flash Immune	



* Length in Meters. Standard cable lengths are 2, 4, 5, 6, 8 and 10 meters. Consult factory for other lengths.

** Standard coupling nut material is nickel plated brass "RKM .."; "RK .." indicates nylon, "RKV .." indicates 316 stainless steel, and "RKVH .." indicates 316 stainless steel hex.

[†] See Section N for **reelfast**® cable information.