

**3 and 5-Wire minifast® Spiral Cordsets, Standard**

- Straight and Right Angle Female Connectors
- NEMA 1, 3, 4, 6P
- IEC IP 67 Protection
- 300 V, 9 A



Housing Style	Part Number	Cable	Application	Pinout
<p><b>RKM ..**</b></p>	RKM 30-2M/S90-SP	AWM PUR Yellow 3x18 AWG 105°C 300 V 9 A 7.3 mm OD	<i>For repetitive 2-wire AC with ground or 3-wire applications</i>	<ol style="list-style-type: none"> <li>GN/YE</li> <li>BN</li> <li>BU</li> </ol>
	RKM 50-1M/S90-SP	AWM PUR Yellow 5x18 AWG 105°C 300 V, 9 A 7.3 mm OD	<i>For repetitive 5-wire AC applications</i>	<ol style="list-style-type: none"> <li>BK</li> <li>BU</li> <li>GN/YE</li> <li>BN</li> <li>WH</li> </ol>
<p><b>WKM ..**</b></p>	WKM 30-2M/S90-SP	AWM PUR Yellow 3x18 AWG 105°C 300 V 9 A 7.3 mm OD	<i>For repetitive 2-wire AC with ground or 3-wire applications</i>	<ol style="list-style-type: none"> <li>GN/YE</li> <li>BN</li> <li>BU</li> </ol>
	WKM 50-1M/S90-SP	AWM PUR Yellow 5x18 AWG 105°C 300 V, 9 A 7.3 mm OD	<i>For repetitive 5-wire AC applications</i>	<ol style="list-style-type: none"> <li>BK</li> <li>BU</li> <li>GN/YE</li> <li>BN</li> <li>WH</li> </ol>

Standard cable lengths are 2 (3-wire) and 1 (5-wire) meter. Consult factory for other lengths.

\*\* Standard coupling nut material is nickel plated brass .. "RKM (WKM) .."; "RKV (WKV) .." indicates 316 stainless steel.

3 and 5-Wire *minifast*® Spiral Cordsets, Standard

- Straight and Right Angle Male Connectors
- NEMA 1, 3, 4, 6P
- IEC IP 67 Protection
- 300 V, 9 A



Housing Style	Part Number	Cable	Application	Pinout
<p>RSM ..**</p>	RSM 30-2M/S90-SP	AWM PUR Yellow 3x18 AWG 105°C 300 V, 9 A 7.3 mm OD	<i>For repetitive 2-wire AC with ground or 3-wire applications</i>	1. GN/YE 2. BN 3. BU 
	RSM 50-1M/S90-SP	AWM PUR Yellow 5x18 AWG 105°C 300 V, 9 A 7.3 mm OD	<i>For repetitive 5-wire AC applications</i>	1. BK 2. BU 3. GN/YE 4. BN 5. WH 
<p>WSM ..**</p>	WSM 30-2M/S90-SP	AWM PUR Yellow 3x18 AWG 105°C 300 V 9 A 7.3 mm OD	<i>For repetitive 2-wire AC with ground or 3-wire applications</i>	1. GN/YE 2. BN 3. BU 
	WSM 50-1M/S90-SP	AWM PUR Yellow 5x18 AWG 105°C 300 V, 9 A 7.3 mm OD	<i>For repetitive 5-wire AC applications</i>	1. BK 2. BU 3. GN/YE 4. BN 5. WH 

Cordsets

Standard cable lengths are 2 (3-wire) and 1 (5-wire) meter. Consult factory for other lengths.

\*\* Standard coupling nut material is nickel plated brass .. "RSM (WSM) .."; "RSV (WSV) .." indicates 316 stainless steel.