

6 and 8-Wire M23 powerfast™ Cordsets, 3-Key

- Female & Male Connectors
- Straight and Right Angles
- IEC IP 67 Protection



Housing Style	Part Number	Cable	Features	Pinout
<p><b>CKM..</b></p>	CKM 622-059-*	<p>AWM TC-ER PVC Yellow 6x12 AWG 90°C 14.7 mm OD 600 V, 30 A Cable #RF51059-*M†</p>		
	CKWM 622-059-*			
<p><b>CKWM..</b></p>	CSSM 622-059-*		<p><i>High Current, 3-Key</i></p>	
	CSSWM 622-059-*			
<p><b>CSSM..</b></p>	CKM 822-287-*	<p>AWM TC-ER PVC Yellow 4x12, 4x18 AWG 90°C 13.2 mm OD 600 V, 30 A (1-4) 300 V, 9 A (A-D) Cable #RF51287-*M†</p>		
	CKWM 822-287-*			
<p><b>CSSWM..</b></p>	CSSM 822-287-*			
	CSSWM 822-287-*			

\* Length in meters. Standard cable lengths are 2, 4, 5, 6, 8 and 10 meters. Consult factory for other lengths. Standard coupling nut material is nickel plated brass.

† See Section N for **reelfast**® cable information.

6 and 8-Wire M23 powerfast™ Cordsets, Shielded, 3-Key

- Female & Male Connectors
- Straight and Right Angles
- IEC IP 67 Protection



Housing Style	Part Number	Cable	Features	Pinout	
<p><b>CKMS..</b></p>	CKMS 622-286-*	<p>AWM TC-ER PVC Yellow 6x12 AWG 90°C 15.5 mm OD 600 V, 30 A Cable #RF51286-*M†</p>	<p><b>High Current, 3-Key, Shielded</b></p>		
	CKWMS 622-286-*				<p><b>CSSMS..</b></p>
<p><b>CSSMS..</b></p>	CKMS 822-288-*	<p>AWM TC-ER PVC Yellow 4x12, 4x18 AWG 90°C 14.7 mm OD 600 V, 30 A (1-4) 300 V, 9 A (A-D) Cable #RF51288-*M†</p>	<p><b>High Current, 3-Key, Shielded</b></p>		
<p><b>CSSWMS..</b></p>	CKWMS 822-288-*				
	<p><b>CSSMS..</b></p>				
<p><b>CSSWMS..</b></p>	CSSWMS 822-288-*				

\* Length in meters. Standard cable lengths are 2, 4, 5, 6, 8 and 10 meters. Consult factory for other lengths.

Standard coupling nut material is nickel plated brass.

† See Section N for **reelfast**® cable information.

Cordsets