

10 and 12-Wire M12 eurofast® Cordsets, "G" Style Large Plug Body

- Straight Male Connector
- NEMA 1, 3, 4, 6P
- IEC IP 68 Protection



Housing Style	Part Number	Cable	Features	Pinout
<p>RSG ..**</p>	RSG 10T-*	AWM PVC Grey 10x24 AWG 105°C 6.0 mm OD Cable #RF51004-*M [†]	<i>flexlife</i> ®	1. WH 6. PK 2. BN 7. BU 3. GN 8. RD 4. YE 9. OG 5. GY 10. TN
	RSG 10T-*/S618	AWM PVC Black 10x24 AWG Foil/Drain 105°C 7.0 mm OD Cable #RF51076-*M [†]	<i>RFI/EMI Shielding</i>	
<p>RSGV ..**</p>	RSG 12T-*	AWM PVC Grey 12x24 AWG 105°C 6.2 mm OD Cable #RF50991-*M [†]	<i>flexlife</i>	1. WH 7. BU 2. BN 8. RD 3. GN 9. OG 4. YE 10. TN 5. GY 11. BK 6. PK 12. VT
	RSG 12T-*/S618	AWM PVC Black 12x24 AWG Foil/Drain 105°C 7.0 mm OD Cable #RF50755-*M [†]	<i>RFI/EMI Shielding</i>	

Cordsets

* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.
 ** Standard coupling nut material is nickel plated brass "RSG .."; "RSGV .." indicates 316 stainless steel.
 † See Section N for **reelfast**® cable information.