

10-Wire M12 eurofast® Cordsets, Standard Plug Body

- Straight Male Connector
- NEMA 1, 3, 4, 6P
- IEC IP 68 Protection
- 60 VAC/75 VDC, 2 A



| Housing Style   | Part Number   | Cable                                                                              | Features            | Pinout |
|-----------------|---------------|------------------------------------------------------------------------------------|---------------------|--------|
| <p>RS ..**</p>  | RS 10T-*      | AWM PVC Grey<br>10x24 AWG<br>105°C<br>6.2 mm OD<br>Cable #RF51004-*M†              | flexlife®           |        |
|                 | RS 10T-*/S90  | AWM PUR Grey<br>10x24 AWG<br>105°C<br>6.2 mm OD<br>Cable #RF51005-*M†              | Cut/Abrasion Immune |        |
|                 | RS 10T-*/S618 | AWM PVC Black<br>10x24 AWG<br>Foil/Drain<br>105°C<br>7 mm OD<br>Cable #RF51076-*M† | RFI/EMI Shielding   |        |
| <p>RSK ..**</p> |               |                                                                                    |                     |        |
| <p>RSV ..**</p> |               |                                                                                    |                     |        |

\* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.

\*\* Standard coupling nut material is nickel plated brass "RS .."; "RSK .." indicates nylon and "RSV .." indicates 316 stainless steel.

† See Section N for **reelfast**® cable information.