

10-Wire M12 eurofast® Cordsets, "C" Style Medium Plug Body

- Right Angle Female Connector
- NEMA 1, 3, 4, 6P
- IEC IP 68 Protection
- 60 VAC/75 VDC, 2 A



| Housing Style | Part Number    | Cable  | Features   | Pinout |
|---------------|----------------|--|--|--------|
|               | WKC 10T-*      | AWM PVC Grey<br>10x24 AWG<br>105°C<br>6.2 mm OD<br>Cable #RF51004-*M†                | <i>flexlife</i> ®                                    |        |
|               | WKC 10T-*/S90  | AWM PUR Grey<br>10x24 AWG<br>105°C<br>6.2 mm OD<br>Cable #RF51005-*M†                | <i>Cut/Abrasion Immune</i>                           |        |
|               | WKC 10T-*/S101 | AWM TPE Black<br>10x24 AWG<br>80°C<br>7.0 mm OD<br>Cable #RF51077-*M†                | <i>flexLife-10, High Flex Over 10 Million Cycles</i> |        |
|               | WKC 10T-*/S618 | AWM PVC Black<br>10x24 AWG<br>Foil/Drain<br>105°C<br>7.0 mm OD<br>Cable #RF51076-*M† | <i>RFI/EMI Shielding</i>                             |        |

\* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.

\*\* Standard coupling nut material is nickel plated brass "WKC .."; "WKCV .." indicates 316 stainless steel.

† See Section N for *reelfast*® cable information.