

12-Wire M12 *euromast*® Cordsets, "C" Style Medium Plug Body

- Right Angle Male Connector
- NEMA 1, 3, 4, 6P
- IEC IP 68 Protection
- 60 VAC/75 VDC, 2 A



Housing Style	Part Number	Cable	Features	Pinout
<p>WSC ..</p> <p>WSCV ..**</p>	WSC 12T-*	AWM PVC Grey 12x24 AWG 105°C 6.2 mm OD Cable #RF50991- <sup>†</sup> M <sup>†</sup>	<i>flexlife</i> ®	
	WSC 12T-*/S90	AWM PUR Grey 12x24 AWG 105°C 6.0 mm OD Cable #RF50990- <sup>†</sup> M <sup>†</sup>	<i>Cut/Abrasion Immune</i>	
	WSC 12T-*/S101	AWM TPE Black 12x24 AWG 105°C 7.0 mm OD Cable #RF50943- <sup>†</sup> M <sup>†</sup>	<i>flexLife-10, High Flex Over 10 Million Cycles</i>	
	WSC 12T-*/S618	AWM PVC Black 12x24 AWG Foil/Drain 105°C 7.0 mm OD Cable #RF50755- <sup>†</sup> M <sup>†</sup>	<i>RFI/EMI Shielding</i>	

Cordsets

\* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.  
 \*\* Standard coupling nut material is nickel plated brass "WSC .."; "WSCV .." indicates 316 stainless steel.  
<sup>†</sup> See Section N for *reelfast*® cable information.