



12-Wire M12 *euromast*® Cordsets, "C" Style Medium Plug Body

- Right Angle Female Connector
- NEMA 1, 3, 4, 6P
- IEC IP 68 Protection
- 60 VAC/75 VDC, 2 A



Housing Style	Part Number	Cable	Features	Pinout
 <p>WKC ..**</p> <p>WKCV ..**</p>	WKC 12T-*	AWM PVC Grey 12x24 AWG 105°C 6.2 mm OD Cable #RF50991- [†] M [†]	<i>flexlife</i> ®	
	WKC 12T-*/S90	AWM PUR Grey 12x24 AWG 105°C 6.0 mm OD Cable #RF50990- [†] M [†]	<i>Cut/Abrasion Immune</i>	
	WKC 12T-*/S101	AWM TPE Black 12x24 AWG 105°C 7.0 mm OD Cable #RF50943- [†] M [†]	<i>flexLife-10, High Flex Over 10 Million Cycles</i>	
	WKC 12T-*/S618	AWM PVC Black 12x24 AWG Foil/Drain 105°C 7.0 mm OD Cable #RF50755- [†] M [†]	<i>RFI/EMI Shielding</i>	

Cordsets

* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.
 ** Standard coupling nut material is nickel plated brass "WKC .."; "WKCV .." indicates 316 stainless steel.
 † See Section N for *reelfast*® cable information.