

2-Wire M12 *eurofast*® Cordsets, Standard Plug Body

- Straight Male Connector
- NEMA 1, 3, 4, 6P
- IEC IP 68 Protection
- 250 VAC/300 VDC, 4 A



| Housing Style | Part Number | Cable | Features | Pinout | |
|---------------|------------------|--|---|------------------------------------|------------------------------------|
| | RS 4.2T-* | AWM PVC Grey 2x20 AWG 105°C 5.2 mm OD Cable #RF50529- [†] M [†] | <i>flexlife</i> ® | 1. N/C 2. N/C 3. BN 4. BU | |
| | RS 4.2T-*/S90 | AWM PUR Grey 2x20 AWG 105°C 5.2 mm OD Cable #RF50772- [†] M [†] | <i>Cut/Abrasion Immune</i> | | |
| | RS 4.2T-*/S748 | AWM PVC Yellow 2x22 AWG 105°C 5.2 mm OD Cable #RF50650- [†] M [†] | | 1. WH 2. N/C 3. N/C 4. BK | |
| | RS 4.21T-*/S1511 | AWM PVC Grey 2x20 AWM PVC 105°C 5.2 mm OD Cable #RF50529- [†] M [†] | <i>flexlife</i> | | |
| | RS 4.21T-* | AWM PVC NAMUR Blue 2x20 AWG 105°C 5.2 mm OD Cable #RF20003- [†] M [†] | | | 1. BN 2. BU 3. N/C 4. N/C |
| | RS 4.21T-*/S90 | AWM PUR NAMUR Blue 2x20 AWG 105°C 5.2 mm OD Cable #RF50657- [†] M [†] | <i>Cut/Abrasion Immune</i> | | |
| | RS 4.22T-* | AWM PVC Grey 2x20 AWG 105°C 5.2 mm OD Cable #RF50529- [†] M [†] | <i>flexlife</i> | | 1. BN 2. N/C 3. BU 4. N/C |
| | | RS 4.23T-* | AWM PVC Grey 2x20 AWG 105°C 5.2 mm OD Cable #RF50529- [†] M [†] | <i>flexlife</i> | 1. BN 2. N/C 3. N/C 4. BU |

* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.
 ** Standard coupling nut material is nickel plated brass "RS .."; "RSK .." indicates nylon and "RSV .." indicates 316 stainless steel.
[†] See Section N for *reelfast*® cable information.