

2-Wire M12 eurofast® Cordsets, Standard Plug Body

- Right Angle Female Connector
- NEMA 1, 3, 4, 6P
- IEC IP 68 Protection
- 250 VAC/300 VDC, 4 A



Housing Style	Part Number	Cable	Features	Pinout	
<p>WK ..**</p>	WK 4.2T-*	AWM PVC Grey 2x20 AWG 105°C 5.2 mm OD Cable #RF50529-*M†	flexlife®	<ol style="list-style-type: none"> 1. N/C 2. N/C 3. BN 4. BU 	
	WK 4.2T-*/S90	AWM PUR Grey 2x20 AWG 105°C 5.2 mm OD Cable #RF50772-*M†	Cut/Abrasion Immune		
	WK 4.2T-*/S748	AWM PVC Yellow 2x22 AWG 105°C 5.2 mm OD Cable #RF50650-*M†			<ol style="list-style-type: none"> 1. WH 2. N/C 3. N/C 4. BK
<p>WKK ..**</p>	WK 4.21T-*/S1511	AWM PVC Grey 2x20 AWM PVC 105°C 5.2 mm OD Cable #RF50529-*M†	flexlife		
	WK 4.21T-*	AWM PVC NAMUR Blue 2x20 AWG 105°C 5.2 mm OD Cable #RF20003-*M†			<ol style="list-style-type: none"> 1. BN 2. BU 3. N/C 4. N/C
	WK 4.21T-*/S90	AWM PUR NAMUR Blue 2x20 AWG 105°C 5.2 mm OD Cable #RF50657-*M†	Cut/Abrasion Immune		
<p>WKV ..**</p>	WK 4.22T-*	AWM PVC Grey 2x20 AWG 105°C 5.2 mm OD Cable #RF50529-*M†	flexlife	<ol style="list-style-type: none"> 1. BN 2. N/C 3. BU 4. N/C 	
	WK 4.23T-*	AWM PVC Grey 2x20 AWG 105°C 5.2 mm OD Cable #RF50529-*M†		<ol style="list-style-type: none"> 1. BN 2. N/C 3. N/C 4. BU 	

* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.
 ** Standard coupling nut material is nickel plated brass "WK .."; "WKK .." indicates nylon and "WKV .." indicates 316 stainless steel.
 † See Section N for reelfast® cable information.