

2 and 3-Wire M12 *eurofast*® Cordsets, "C" Style Medium Plug Body

- Straight Female Connector
- NEMA 1, 3, 4, 6P
- IEC IP 68 Protection
- 250 V, 4 A



Housing Style	Part Number	Cable	Features	Pinout
<p>RKC ..** 1.654 [42.0] 0.589 [15.0] M12x1 ANTI-VIBRATION DETENT</p> <p>RKC V ..** 1.654 [42.0] 0.591 [15.0] M12x1</p>	RKC 4.2T-*	AWM PVC Yellow 2x18 AWG 105°C 7.3 mm OD Cable #RF50511- <i>M</i> [†]	<i>flexlife</i> ®	1. N/C 2. N/C 3. BN 4. BU
	RKC 4.2T-*/CS10191	AWM PVC NAMUR Blue 2x18 AWG 105°C 7.2 mm OD Cable #RF50843- <i>M</i> [†]	<i>flexlife</i> , <i>Black Plug Body</i>	1. N/C 2. N/C 3. BN 4. BU
	RKC 4T-*	AWM PVC Yellow 3x18 AWG 105°C 7.3 mm OD Cable #RF50513- <i>M</i> [†]	<i>flexlife</i>	1. BN 2. N/C 3. BU 4. BK
	RKC 4T-*/S1062	AWM PVC Yellow 3x18 AWG 105°C 7.3 mm OD Cable #RF50513- <i>M</i> [†]	<i>flexlife</i> ® Cable, <i>PVC plug body with PVC contact carriers</i>	

* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.

** Standard coupling nut material is nickel plated brass "RKC .."; "RKC V .." indicates 316 stainless steel.

† See Section N for *reelfast*® cable information.