

3 and 4-Wire M12 *eurofast*® Cordsets, "G" Style Large Plug Body

- Straight Female Connector
- NEMA 1, 3, 4, 6P
- IEC IP 68 Protection
- 250 V, 4 A



Housing Style	Part Number	Cable	Features	Pinout	
 	RKG 4T-*	AWM PVC Yellow 3x18 AWG 105°C 7.3 mm OD Cable #RF50513- <sup>†</sup> M <sup>†</sup>	<i>flexlife</i> ®	1. BN 2. N/C 3. BU 4. BK	
	RKG 4T-*/S600	SJOOW CPE Yellow 3x18 AWG 105°C 8.0 mm OD Cable #RF50654- <sup>†</sup> M <sup>†</sup>	<i>Weld Flash Immune, Flame Resistance</i>		
	RKG 4.4T-*	AWM PVC Yellow 4x18 AWG 105°C 7.3 mm OD Cable #RF50579- <sup>†</sup> M <sup>†</sup>	<i>flexlife</i>		
	RKG 4.4T-*/S90	AWM PUR Yellow 4x18 AWG 105°C 7.3 mm OD Cable #RF50544- <sup>†</sup> M <sup>†</sup>	<i>Cut/Abrasion Immune</i>		
	RKG 4.4T-*/S101/S849	AWM TPE Grey 4x22 AWG 105°C 5.2 mm OD Cable #RF50941- <sup>†</sup> M <sup>†</sup>	<i>flexlife-10, High Flex - Over 10 Million Cycles</i>		
	RKG 4.4T-*/S101	AWM TPE Yellow 4x18 AWG 105°C 7.2 mm OD Cable #RF50968- <sup>†</sup> M <sup>†</sup>			1. BN 2. WH 3. BU 4. BK
	RKG 4.4T-*/S529	AWM PUR/Heavy Braid Double Jacket Yellow 4x20 AWG 105°C 5.8 mm OD Cable #RF50526- <sup>†</sup> M <sup>†</sup>	<i>Cut/Abrasion Immune, Braided Mechanical Shield</i>		
	RKG 4.4T-*/S1587	AWM TPE Yellow 4x18 AWG 105°C 7.3 mm OD Cable #RF50956- <sup>†</sup> M <sup>†</sup>	<i>weldlife, Weld Flash Immune</i>		
	RKG 4.4T-*/S1052/S1587	AWM TPE Grey 4x18 AWG 105°C 7.2 mm OD Cable #RF51273- <sup>†</sup> M <sup>†</sup>	<i>weldlife, Weld Flash Immune</i>		

\* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.

\*\* Standard coupling nut material is nickel plated brass "RKG .."; "RKGV .." indicates 316 stainless steel.

<sup>†</sup> See Section N for *reelfast*® cable information.

## 4, 5, 6 and 8-Wire M12 eurofast® Cordsets, "G" Style Large Plug Body

- Straight Female Connector
- NEMA 1, 3, 4, 6P
- IEC IP 68 Protection



Housing Style	Part Number	Cable	Features	Pinout	
	RKG 4.4T-*/S600	SJOOW CPE Yellow 4x18 AWG 105°C 8.5 mm OD Cable #RF50644- *M†	<i>Weld Flash Immune Flame Resistance</i>	1. BN 2. WH 3. BU 4. BK	
	RKG 4.5T-*	AWM PVC Grey 5x22 AWG 105°C, 250 V, 4 A 5.7 mm OD Cable #RF50543- *M†	<i>flexlife®</i>	1. BN 2. WH 3. BU 4. BK 5. CY	
	RKG 4.5T-*/S90/S715	AWM PUR Yellow 5x18 AWG 105°C, 250 V, 4 A 7.2 mm OD Cable #RF50751- *M†	<i>Cut/Abrasion Immune</i>	1. BN 2. WH 3. BU 4. BK 5. GN/YE	
	RKG 4.5T-*/S600	SJOOW CPE Yellow 5x18 AWG, 105°C 250 V, 4A 9.4 mm OD Cable #RF50937- *M†	<i>Weld Flash Immune, Flame Resistance</i>	1. BN 2. WH 3. BU 4. BK 5. CY	
	RKG 6T-*	AWM PVC Grey 6x24 AWG, 105°C 60 VAC/75 VDC, 2 A 5.7 mm OD Cable #RF50608- *M†	<i>flexlife</i>	1. BN 2. WH 3. BU 4. BK 5. CY 6. PK	
	RKG 6T-*/S90	AWM PUR Grey 6x24 AWG, 105°C 60VAC/75VDC, 2 A 5.7 mm OD Cable #RF50646- *M†	<i>Cut/Abrasion Immune</i>	1. WH 2. BN 3. GN 4. YE 5. CY 6. PK 7. BU 8. RD	
	RKG 8T-*	AWM PVC Grey 8x24 AWG, 105°C 60 VAC/75 VDC, 2 A 5.7 mm OD Cable #RF50753- *M†	<i>flexlife</i>	1. WH 2. BN 3. GN 4. YE 5. CY 6. PK 7. BU 8. RD	
	RKG 8T-*/S90	AWM PUR Grey 8x24 AWG, 105°C 60 VAC/75 VDC, 2 A 5.7 mm OD Cable #RF50984- *M†	<i>Cut/Abrasion Immune</i>		

Cordsets

\* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.  
 \*\* Standard coupling nut material is nickel plated brass "RKG .."; "RKGV .." indicates 316 stainless steel.  
 † See Section N for **reelfast**® cable information.