





3-Wire M12 eurofast® Cordsets, Standard Plug Body

- Straight Male Connector
- NEMA 1, 3, 4, 6P
- IEC IP 68 Protection
- 250 VAC/300 VDC, 4 A



Housing Style	Part Number	Cable	Features	Pinout	
RS ..**  RSK ..**  RSV ..** 	RS 4T-*	AWM PVC Grey 3x20 AWG 105°C 5.2 mm OD Cable #RF50528-*M†	flexlife®	 1. BN 2. N/C 3. BU 4. BK	
	RS 4T-*/S90	AWM PUR Grey 3x20 AWG 105°C 5.2 mm OD Cable #RF50518-*M†	Cut/Abrasion Immune		
	RS 4T-*/S101	AWM TPE Grey 3x20 AWG 105°C 5.7 mm OD Cable #RF50940-*M†	flexlife-10, High Flex Over 10 Million Cycles		
	RS 4T-*/S529	AWM PUR/Heavy Braid Double Jacket Yellow 3x20 AWG 105°C 5.2 mm OD Cable #RF50832-*M†	Cut/Abrasion Immune Braided Mechanical Shield		
	RS 4T-*/S824	PLTC AWM PVC Grey 3x20 AWG 105°C 5.2 mm OD Cable #RF50829-*M†	Tray Rated		
	RS 4T-*/S715	AWM PVC Yellow 3x20 AWG 105°C 5.2 mm OD Cable #RF50674-*M†	flexlife		
	RS 4T-*/S760	AWM PVC Black 3x20 AWG 105°C 5.2 mm OD Cable #RF50795-*M†			
	RS 4T-*/S618	AWM PVC Grey 3x20 AWG Foil/Drain 105°C 5.7 mm OD Cable #RF50611-*M†	RFI/EMI Shielding		

Cordsets

* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.

** Standard coupling nut material is nickel plated brass "RS .."; "RSK .." indicates nylon and "RSV .." indicates 316 stainless steel.

† See Section N for **reelfast**® cable information.