

3-Wire M12 eurofast® Cordsets with LEDs

- Right Angle Female Connector
- NEMA 1, 3, 4, 6P
- IEC IP 68 Protection
- 10-30 VDC, 4 A



Housing Style	Part Number	Cable	Features	Pinout
	WK 4T-**-P7X2	AWM PVC Grey 3x20 AWG 105°C 5.2 mm OD Cable #RF50528- [†] M [†]	PNP Signal, flexlife®	
	WK 4T-**-N7X2	AWM PVC Grey 3x20 AWG 105°C 5.2 mm OD Cable #RF50528- [†] M [†]	NPN Signal, flexlife	
	WK 4T-**-P7X2/S90	AWM PUR Grey 3x22 AWG 105°C 5.2 mm OD Cable #RF50518- [†] M [†]	PNP Signal, Cut/Abrasion Immune	
	WK 4T-**-N7X2/S90	AWM PUR Grey 3x22 AWG 105°C 5.2 mm OD Cable #RF50518- [†] M [†]	NPN Signal, Cut/Abrasion Immune	
	WK 4T-**-P7X2/S101	AWM TPE Grey 3x20 AWG 105°C 5.7 mm OD Cable #RF50940- [†] M [†]	PNP Signal, flexlife-10, High Flex - Over 10 Million Cycles	
	WK 4T-**-N7X2/S101	AWM TPE Grey 3x20 AWG 105°C 5.7 mm OD Cable #RF50940- [†] M [†]	NPN Signal, flexlife-10, High Flex - Over 10 Million Cycles	
	WK 4T-**-P7X2/S618	AWM PVC Grey 3x20 AWG 105°C 5.7 mm OD Cable #RF50611- [†] M [†]	PNP Signal, EMI/RFI Protection	
	WK 4T-**-N7X2/S618	AWM PVC Grey 3x20 AWG 105°C 5.7 mm OD Cable #RF50611- [†] M [†]	NPN Signal ,EMI/RFI Protection	
	WK 4T-**-P7X2/S715	AWM PVC Yellow 3x20 AWG 105°C 5.2mm OD Cable #RF50674- [†] M [†]	PNP Signal, flexlife	
	WK 4T-**-N7X2/S715	AWM PVC Yellow 3x20 AWG 105°C 5.2mm OD Cable #RF50674- [†] M [†]	NPN Signal, flexlife	

* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.

** Standard coupling nut material is nickel plated brass "WK .."; "WKV .."; indicates 316 stainless steel.

[†] See Section N for reelfast® cable information.

See page D88 for LED diagrams.