

3-Wire M12 eurofast® Cordsets with LEDs

- Straight Female Connector
- NEMA 1, 3, 4, 6P
- IEC IP 68 Protection
- 10-30 VDC, 4 A



Housing Style	Part Number	Cable	Features	Pinout	
	RKE 4T-*/-P7X2	AWM PVC Grey 3x20 AWG 105°C 5.2 mm OD Cable #RF50528-*M†	PNP Signal, flexlife®	1. BN 2. N/C 3. BU 4. BK	
	RKE 4T-*/-N7X2	AWM PVC Grey 3x20 AWG 105°C 5.2 mm OD Cable #RF50528-*M†	NPN Signal, flexlife		
	RKE 4T-*/-P7X2/S90	AWM PUR Grey 3x22 AWG 105°C 5.2 mm OD Cable #RF50518-*M†	PNP Signal, Cut/Abrasion Immune		
	RKE 4T-*/-N7X2/S90	AWM PUR Grey 3x22 AWG 105°C 5.2 mm OD Cable #RF50518-*M†	NPN Signal, Cut/Abrasion Immune		
	RKE 4T-*/-P7X2/S715	AWM PVC Yellow 3x20 AWG 105°C 5.2 mm OD Cable #RF50674-*M†	PNP Signal, Flexlife		
	RKE 4T-*/-N7X2/S715	AWM PVC Yellow 3x20 AWG 105°C 5.2 mm OD Cable #RF50674-*M†	NPN Signal, Flexlife		
	RKE 4T-*/-P7X2/S824	PLTC PVC Grey 3x20 AWG 105°C 5.2 mm OD Cable #RF50829-*M†	PNP Signal, Tray Rated		
	RKE 4T-*/-N7X2/S824	PLTC PVC Grey 3x20 AWG 105°C 5.2 mm OD Cable #RF50829-*M†	NPN Signal, Tray Rated		

* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.

** Standard coupling nut material is nickel plated brass "RKE..".

† See Section N for **reelfast**® cable information.

See page D88 for LED diagrams.